LIMITED ACCESS HIGHWAY

By Resolution of Highway Commission dated October 4, 1956

FOR INDEX OF SHEETS SEE SHEET 1B

DESIGN PACKAGE OPENROADS/GEOPAK.

Description Reference

STATE LINE COUNTY LINE

FENCE LINE

WATER LINE

TRAVELED WAY

RETAINING WALL

GUARD RAIL

RAILROADS

BRIDGES

HEDGE

TREES

CULVERTS

POWER POLES

HEAVY WOODS

GROUND ELEVATION

GRADE ELEVATION

GAS LINE

CITY, TOWN OR VILLAGE RIGHT OF WAY LINE

SANITARY SEWER LINE

BASE OR SURVEY LINE

LEVEE OR EMBANKMENT

TELEPHONE OR TELEGRAPH POLES

TELEPHONE OR TELEGRAPH LINES

UNFENCED PROPERTY LINE

ELECTRIC UNDERGROUND CABLE

Mile Mark 32J97 I-8I NB

Sta.107+20 I-81 NB Constr.BL

CONVENTIONAL SIGNS

GEOPAK Computer Identification No. UPC 116156

THIS PROJECT WAS DEVELOPED UTILIZING THE DEPARTMENT'S ENGINEERING



COMMONWEALTH OF VIRGINIA

DEPARTMENT OF TRANSPORTATION

PLAN AND PROFILE OF PROPOSED STATE HIGHWAY

WASHINGTON COUNTY 1-81 NORTHBOUND TRUCK CLIMBING LANE FROM: MILE MARK 32.197 TO: MILEMARK 33.5/9

FEDERAL AID PROJECT FHWA-534 DATA 11103 NHPP-081-1 () UPC NO. 116156 VA.

STATE PROJECT (SEE TABULATION BELOW FOR SECTION NUMBERS) (SEE TABULATION BELOW FOR SECTION NUMBERS)

F	UNCT	IONAL CLASSIFIC	CATION AND TRAFFIC	DATA					
SB I-81 - (GS-INT) INTERSTATE - ROLLING - 75 MPH MIN. DESIGN SPEED									
		DESIGN VE	HICLE - WB-67						
		r: MILE MARK 32.197 To: MILE MARK 33.519							
ADT (2018)	16,04	6,040							
ADT (2045)	21,40	21,404							
DHV	1,170								
D (%) (design hour)									
T (%) (design hour)	17%	17%							
V (MPH)	See Pl	See Plan and Profile Sheets for Horizontal and Vertical Curve Design Speed							
E	XCEPTIONS TO MAINLINE DESIGN SPEED								
Sta. To Sta.		Approval Date							
157+94.00		60	Vertical Curve Radius						
118+00.00 to 129+0	00.00		Superelevation Rate						

PH PLANS

THESE PLANS ARE UNFINISHED AND UNAPPROVED AND ARE NOT TO BE USED FOR ANY TYPE OF CONSTRUCTION OR THE ACQUISITION OF RIGHT OF WAY.

10 CHILHOWIE 120 *Project 172+00.00* oject 20.00 *Project* 177+00.00 0081-095-829, RW-201 D Q 0081-095-829, C-501 THE COMPLETE ELECTRONIC PDF VERSION OF THE PLAN ASSEMBLY AS AWARDED, HAS BEEN <u>SEALED AND SIGNED</u> USING DIGITAL 0081-095-829, PE-101

SIGNATURES AND THE OFFICIAL PLAN ASSEMBLY IN ELECTRONIC FORMAT IS STORED IN THE VDOT CENTRAL OFFICE PLAN LIBRARY, INCLUDING ALL SUBSEQUENT REVISIONS, WILL BE THE OFFICIAL CONSTRUCTION PLANS. FOR INFORMATION RELATIVE TO ELECTRONIC FILES AND LAYERED PLANS, SEE THE GENERAL NOTES.

••••

D=======

· • • • •

-0 0 0 0

DATUM LINE \$

DESIGN FEATURES RELATING TO CONSTRUCTION OR TO REGULATION AND CONTROL OF TRAFFIC MAY BE SUBJECT TO CHANGE AS DEEMED NECESSARY BY THE DEPARTMENT.

THIS PROJECT IS TO BE CONSTRUCTED IN ACCORDANCE WITH THE DEPARTMENT'S 2020 ROAD AND BRIDGE SPECIFICATIONS, 2016 ROAD AND BRIDGE STANDARDS, 2009 MUTCD, 2011 VIRGINIA SUPPLEMENT TO THE MUTCD, 2011 VIRGINIA WORK AREA PROTECTION MANUAL AND AS AMENDED BY CONTRACT PROVISIONS AND THE COMPLETE ELECTRONIC PDF VERSION OF THE PLAN ASSEMBLY.

ALL CURVES ARE TO BE SUPERELEVATED, TRANSITIONED AND WIDENED IN ACCORDANCE WITH STANDARD TC-5.11, EXCEPT WHERE OTHERWISE NOTED.

THE <u>ORIGINAL</u> APPROVED TITLE SHEET(S), INCLUDING ORIGINAL SIGNATURES, ARE FILED IN THE VDOT CENTRAL OFFICE PLAN LIBRARY. ANY MISUSE OF ELECTRONIC FILES, INCLUDING SCANNED SIGNATURES, IS ILLEGAL AND ENFORCED TO THE FULL EXTENT OF THE LAW.

Washington County Population 54,402 (2018 Census)

STATE PROJECT	SECTION	FEDERAL AID PROJECT NO.	TYPE CODE	UPC NO.	EQUALITIES	LENGTH I BRID(NCLUDING GE(S)		XCLUDING GE(S)	TYPE PROJECT	DESCRIPTION
NO.		TROOLET NO.	CODE	140.	FEET	FEET	MILES	FEET	MILES	TROOLOT	
-829	PE-101	NHPP-081-1 (362)		116156		6,980.00	1.322	6,980.00	1.322	PRELIM. ENGR.	Fr: MILE MARK 32.197 To: MILE MARK 33.519
.095	RW- 201			116156		5,048.30	0.956	5,048.30	0.956	RIGHT OF WAY	Fr: MILE MARK 32.428 To: MILE MARK 33.384
0081-	C-501		1000	116156		5,400.00	1.023	5,400.00	1.023	CONSTR.	Fr: MILE MARK 32.402 To: MILE MARK 33.425

Project Lengths are based on I-81 NBL Construction Baseline.

TIER 2 PROJECT RECOMMENDED FOR APPROVAL FOR RIGHT OF WAY ACQUISITION INFRASTRUCTURE INVESTMENT DIRECTOR STATE LOCATION AND DESIGN ENGINEER CHIEF FINANCIAL OFFICER CHIEF ENGINEER

APPROVED FOR RIGHT OF WAY ACQUISITION CHIEF OF POLICY

RECOMMENDED FOR APPROVAL FOR CONSTRUCTION INFRASTRUCTURE INVESTMENT DIRECTOR STATE LOCATION AND DESIGN ENGINEER

REVISED

STATE STRUCTURE AND BRIDGE ENGINEER CHIEF FINANCIAL OFFICER

APPROVED FOR CONSTRUCTION CHIEF ENGINEER

APPROVED DIVISION ADMINISTRATOR FEDERAL HIGHWAY ADMINISTRATION U.S. DEPARTMENT OF TRANSPORTATION Copyright 2020, Commonwealth of Virginia

0081-095-829


DESIGN

DISTRICT

BRIST OL

0.5 MI

LIMITED ACCESS HIGHWAY By Resolution of Highway Commission dated October 4, 1956



PROJECT MANAGER <u>James Jones, L.S.(276) 696-3257 (Bristol)</u> SURVEYED BY, DATE <u>Woolpert Jac., (757) 549-3549 (Nov. 24, 2019)</u>

DESIGN BY *Tamara Pritchard, P.E. (276). 696-3249 (Bristol)*SUBSURFACE UTILITY BY, DATE *Woolpert Inc., (757). 549-3549 (Nov., 24, 2019)*.

LIMITED ACCESS HIGHWAY By Resolution of Highway Commission dated October 4, 1956

MAY BE SUBJECT TO CHANGE AS DEEMED NECESSARY BY THE DEPARTMENT

DESIGN FEATURES RELATING TO CONSTRUCTION
OR TO REGULATION AND CONTROL OF TRAFFIC

INDEX OF SHEETS

SHEET NO.	DESCRIPTION
l	TITLE SHEET
/A	LOCATION MAP
IB	INDEX OF SHEETS
IC	RIGHT OF WAY DATA SHEET
ID	REVISION DATA SHEET
IF(I)-IF2I)	SURVEY ALIGNMENT DATA SHEET
IG	CONSTRUCTION ALIGNMENT DATA SHEET
IJ(I)-IJ(I7)	TRANSPORTATION MANAGEMENT PLAN
2	GENERAL NOTES
2A(I)	TYPICAL SECTIONS
2B(I) -2B(4)	STORMWATER POLLUTION PREVENTION PLANS
2K(I)	SEDIMENT TRAP DETAIL
3	PLAN STA.102+00.00 TO STA.112+50.00
4	PLAN STA.112+50.00 TO STA.124+50.00
4A	PROFILE STA.118+00.00 TO STA.124+50.00
4B	EROSION & SEDIMENT CONTROL PLAN - PHASE I
4C	EROSION & SEDIMENT CONTROL PLAN - PHASE II
4RW	RIGHT OF WAY PLAN STA. 118+00.00 TO STA. 124+50.00
5	PLAN STA.124+25.00 TO STA.137+50.00
5A	PROFILE STA.124+25.00 TO STA.137+50.00
5B	EROSION & SEDIMENT CONTROL PLAN - PHASE I
5C	EROSION & SEDIMENT CONTROL PLAN - PHASE II
5RW	RIGHT OF WAY PLAN STA.124+25.00 TO STA.137+50.00
6	PLAN STA.137+50.00 TO STA.150+50.00
6A	PROFILE STA.137+50.00 TO STA.150+50.00
6B	EROSION & SEDIMENT CONTROL PLAN - PHASE I
6C	EROSION & SEDIMENT CONTROL PLAN - PHASE II
6RW	RIGHT OF WAY PLAN STA.137+50.00 TO STA.150+50.00
7	PLAN STA.150+50.00 TO STA.163+50.00
7A	PROFILE STA.150+50.00 TO STA.163+50.00
7B	EROSION & SEDIMENT CONTROL PLAN - PHASE I
7C	EROSION & SEDIMENT CONTROL PLAN - PHASE II
8	PLAN STA.163+50.00 TO STA.172+00.00
8A	PROFILE STA.163+50.00 TO STA.172+00.00
8B	EROSION & SEDIMENT CONTROL PLAN - PHASE I
8C	EROSION & SEDIMENT CONTROL PLAN - PHASE II
8RW	RIGHT OF WAY PLAN STA.163+50.00 TO STA.172+00.00

TOTAL CROSS SECTION SHEETS 36 (SEE CROSS SECTION SHEET NUMBER I FOR INDEX OF SHEETS)

PH PLANS

THESE PLANS ARE UNFINISHED AND UNAPPROVED AND ARE NOT TO BE USED FOR ANY TYPE OF CONSTRUCTION OR THE ACQUISITION OF RIGHT OF WAY.

PROJECT SHEET NO. 1/B

d116156001c.dan

LIMITED ACCESS HIGHWAY

By Resolution of Highway Commission dated October 4, 1956

PROJECT MANAGER <u>James Jones, L.S.(276) 696-3257 (Bristol)</u>
SURVEYED BY, DATE <u>Woolpert Inc., (757) 549-3549 (Nov.24,2019)</u>
DESIGN BY <u>Tamara Pritchard, P.E.(276) 696-3249 (Bristol)</u>
SUBSURFACE UTILITY BY, DATE <u>Woolpert Inc., (757) 549-3549 (Nov.24,2019)</u>

PRELIMINARY RIGHT OF WAY DATA SHEET

PH PLANS

THESE PLANS ARE UNFINISHED AND UNAPPROVED AND ARE NOT TO BE USED FOR ANY TYPE OF CONSTRUCTION OR THE ACQUISITION OF RIGHT OF WAY.

REVISED	STATE		STATE	SHEET NO.
	STATE	ROUTE	PROJECT	SHEET NO.
	VA.	81	0081-095-829,PE-101, RW-201,C-501	IC

DESIGN FEATURES RELATING TO CONSTRUCTION OR TO REGULATION AND CONTROL OF TRAFFIC MAY BE SUBJECT TO CHANGE AS DEEMED NECESSARY BY THE DEPARTMENT

City/County: Washington

														ty/ County:		
		Ī	T										UF	PC No.: 116	156	
PARCEI		CHEET	SHEET													
PARCEL NO.	LANDOWNER	SHEET NO.	TOTAL	FFF	TAKING	PRESCRIPTIVE R/W	FEE RE	MAINDER			EASEMENTS		1		PROFFERS	
										IANENT	UTILITY	TEMPORARY TEMPORARY(ENTRANCES)				
			ACRES OR SQUARE FEET	ACRES OR	HECTARES/	ACRES OR HECTARES/	ACRES OR	HECTARES/	ACRES OR	HECTARES/	ACRES OR HECTARES/	ACRES OR HECTAR	ES/ ACRES OR	HECTARES/	\/FQ / \/Q	
			ACRES OR SQUARE FEET	SQ. FEET	SQ. METERS	SQ. FEET OR SQ. METERS	SQ. FEET	OR SQ. METERS	SQ. FEET	OR SQ. METERS	SQ. FEET SQ. METERS	SQ. FEET SQ. MET	SQ. FEET	OR SQ. METERS	YES / NO	
001	DAN G.COALSON	4,5	2.39 AC				2.39 AC		8,831 SF	SQT ME TELLS				og. Werens		
002	RONNIE C.WIDENER	5	2.31 AC				2.31 AC					6,176 SF				
003	LOIS M.FARIS	7,8	60.28 AC				60.28 AC					407 SF				
	EOIS IN.I AINS	7,0	00.20 AC				00.20 AC					701 31				
			I .	1		<u> </u>	1									PROJECT
																0081-095-829

S/GN

DIST

dll6l5600ld.dgn

Plotted By: elilley
I IMITED ACCESS HIGHWAY By Resolution of Highway Commission

				LIMITED ACCESS HIGHWAY By Resolution of Highway Commission dated October 4, 1956
PROJECT MANAGER_Jim_Jones, L.S. (276) 696-3257 (Bristol) SURVEYED BY, DATE <u>Woolpert Inc., (757) 549-3549 (Nov. 24. 2019)</u> DESIGN BY <u>Tamara_Pritchard, P.E. (276) 696-3249 (Bristol)</u> SUBSURFACE UTILITY BY, DATE <u>Woolpert Inc., (757) 549-3549 (Nov. 24, 2019)</u>				REVISED STATE STATE ROUTE PROJECT SHEET N
DESIGN BY Tamara Pritchard, P.E. (276) 696-3249 (Bristol)			PH PLANS	1.0000
SUBSURFACE UTILITY BY, DATE <u>Woolpert Inc., (757) 549-3549 (Nov. 24, 2019)</u>	DEVICION	DATA SHEET		VA. 81 0081-095-829, PE-101, ID
			THESE PLANS ARE UNFIN	NISHED RW-201, C-501
			AND UNAPPROVED AND AF	₹E NOT
State Project: 0081-095-829, PE-101, RW-201, C-501 Federal Project: NHPP-081-1(362)			TO BE USED FOR ANY TY	PE DESIGN FEATURES RELATING TO CONSTRUCTION OR TO REGULATION AND CONTROL OF TRAFFIC
Federal Project: NHPP-081-1(362) From: MILE MARK 32,197			OF CONSTRUCTION OR TH	1L MAY BE SUBJECT TO CHANGE AS DEFMED
To: MILE MARK 33.519			ACQUISITION OF RIGHT O	NECESSARY BY THE DEPARTMENT
UPC Number: 116156				
				DDO IECT QUEET NO
				PROJECT SHEET NO 0081-095-829 I:D

PROJECT MANAGER <u>James Jones, L.S. (276) 696-3257 (Bristol)</u>

SURVEYED BY, DATE *Woolpert.Inc.*.(757)_549-3549_(Nov.24,2019)______

DESIGN BY *Tamara Pritchard, P.E. (276) 696-3249 (Bristol)* SUBSURFACE UTILITY BY, DATE *Woolpert Inc. (757) 549-3549 (Nov. 24. 2019)*.

VDOT Project Coordinates (2014)

East (X): N/A ft.

North (Y): N/A ft.

Elevation : N/A ft.

Project Specific Combined Scale

Factor: I.<u>000000000</u> (9 Decimal Places)

Latitude : <u>36</u>° <u>46</u>′ <u>53,17174</u>" N (5 Decimal Places)

Longitude: 81° 44′ 18.45225" W (5 Decimal Places)

Geoid : <u>12B</u>

Geoid Separation (N): <u>-101.482</u>

Control Based On: OPUS Project

Azimuth to Station : <u>902</u> is <u>68° 44′ 50</u>″

Ellipsoid Height(h):<u>1872.69</u>

Horizontal Datum : <u>NAD83</u>

Vertical Datum : <u>NAVD88</u>

Azimuth to Station : <u>903</u> is <u>260</u>° <u>57</u>′ <u>14</u>"

LIMITED ACCESS HIGHWAY By Resolution of Highway Commission dated October 4, 1956 REVISED ROUTE PROJECT

0081-095-829,PE-101, *IF(I)* VA. RW-201, C-501

DESIGN FEATURES RELATING TO CONSTRUCTION OR TO REGULATION AND CONTROL OF TRAFFIC MAY BE SUBJECT TO CHANGE AS DEEMED NECESSARY BY THE DEPARTMENT

PH PLANS

THESE PLANS ARE UNFINISHED AND UNAPPROVED AND ARE NOT TO BE USED FOR ANY TYPE OF CONSTRUCTION OR THE ACQUISITION OF RIGHT OF WAY.

SURVEY ALIGNMENT DATA SHEET

LD-200 (REV. 10/2014)


LD-200 (REV. 10/2014)

LD-200 (REV. 10/2014)

,	nsportation Horizontal Control 901 Date : <u>II-19-2019</u>
ect Coordinates (2014) t(X): <u>N/A</u> ft. h(Y): <u>N/A</u> ft. ation: <u>N/A</u> ft.	VA State Plane Coordinates: NAD 83-U.S. Survey Feet East (X): 10534670.036 ft. North (Y): 3460249.009 ft. Ortho. Elevation (H): 1974.17 ft. Zone: North = South X (place an 'X' beside one)
Specific Combined Scale 2000000 (9 Decimal Places)	Project Information Project Number : <u>PEI2-96I-I88, PIOI</u>
17174" N (5 Decimal Places)	Route : <u>I-8I (NBL)</u> City/County : <u>Washington</u>


Established By: <u>Woolpert</u> To convert Virginia State Plane Coordinates to VDOT Project Coordinates, use the following formula: Year : <u>2011-2010.00</u> * Multiply the Easting And Northing Values (For Both Zones) by the Project Specific Combined Scale Factor. (Located above left) * Reverse this Procedure to convert VDOT Project

Coordinates (2014) to NAD 83 - U.S. Survey Feet




Virginia Department of Tran Control Station 1.D.: 90	nsportation Horizontal Control 04 Date : <u>II-19-2019</u>
VDOT Project Coordinates (2014) East (X): N/A ft. North (Y): N/A ft. Elevation: N/A ft.	VA State Plane Coordinates: NAD 83-U.S. Survey Feet East (X): 10539140.939 ft. North (Y): 3462074.441 ft. Ortho. Elevation (H): 2047.10 ft. Zone: North South X (place an 'X' beside one)
Project Specific Combined Scale Factor: I. <u>000000000</u> (9 Decimal Places)	Project Information Project Number : <u>PEI2-96I-188, PIOI</u>
Latitude : <u>36° 47′ [2,72339"</u> N (5 Decimal Places) Longitude : <u>81° 43′ 24,29247"</u> W (5 Decimal Places)	Route : <u>I-8I (NBL)</u> City/County : <u>Washington</u> Established By : <u>Woolpert</u>
Geoid Separation (N):-101.47 Ellipsoid Height (h):1945.63 Horizontal Datum: NAD83 Year: 2011-2010.00 Vertical Datum: NAVD88 Geoid: 12B	To convert Virginia State Plane Coordinates to VDOT Project Coordinates, use the following formula: * Multiply the Easting And Northing Values (For Both Zones) by the Project Specific Combined Scale Factor.

(Located above left)




LD-200 (REV. 10/2014) Virginia Department of Transportation Horizontal Control Control Station 1.D.: <u>902</u> Date: <u>II-I9-2019</u> VA State Plane Coordinates : NAD 83- U.S. Survey Feet VDOT Project Coordinates (2014) East (X): <u>10535245.787</u> ft. East (X): N/A ft. North (Y): <u>3460472.938</u> ft. North $(Y): \underline{N/A} ft.$ Ortho. Elevation (H): 1967.03 ft. Elevation : N/A ft. Zone: North _ South X (place an 'X' beside one) Project Specific Combined Scale Project Information Factor: I.<u>000000000</u> (9 Decimal Places) Project Number : <u>PEI2-96I-I88, PI0I</u> Route: <u>I-81 (NBL)</u> City/County: <u>Washington</u> Latitude : <u>36</u>° <u>46</u>′ <u>55.57980</u>" N (5 Decimal Places) Established By: Woolpert Longitude : <u>81° 44′ 11.47343"</u> W (5 Decimal Places) Geoid Separation (N): <u>-101.48</u> To convert Virginia State Plane Coordinates to VDOT Project Coordinates, use the following formula: Ellipsoid Height (h): <u>1865.549</u> Horizontal Datum : <u>NAD83</u> Year : <u>2011-2010.00</u> * Multiply the Easting And Northing Values (For Both Vertical Datum : <u>NAVD88</u> Geoid : <u>12B</u> Zones) by the Project Specific Combined Scale Factor. (Located above left) Azimuth to Station : <u>901</u> is <u>248° 44</u>′ <u>50</u>″ Control Based On: OPUS Project * Reverse this Procedure to convert VDOT Project Coordinates (2014) to NAD 83 - U.S. Survey Feet CORS Stations VABG, WVAT, LSO4, NCSR DETAILED SKETCH (Not to Scale)



·	nsportation Horizontal Control 5 Date: <u>II-19-2019</u>
VDOT Project Coordinates (2014) East (X): <u>N/A</u> ft. North (Y): <u>N/A</u> ft. Elevation: <u>N/A</u> ft.	VA State Plane Coordinates: NAD 83-U.S. Survey Feet East (X): 10542689.740 ft. North (Y): 3462560.641 ft. Ortho. Elevation (H): 2086.52 ft. Zone: North = South X (place an 'X' beside one)
Project Specific Combined Scale Factor: 1.000000000 (9 Decimal Places) Latitude: 36° 47′ 18.72372" N (5 Decimal Places) Longitude: 81° 42′ 40.89482" W (5 Decimal Places)	Project Information Project Number: <u>PEI2-96I-I88, PIOI</u> Route: <u>I-8I (NBL)</u> City/County: <u>Washington</u> Established By: <u>Woolpert</u>
Geoid Separation (N):-IOI,47 Ellipsoid Height (h): I985.05 Horizontal Datum: NAD83 Year: 2011-2010.00 Vertical Datum: NAVD88 Geoid: I2B Azimuth to Station: 906 is 100° 05′ 28" Control Based On: OPUS Project CORS Stations VABG,WVAT,LSO4,NCSR	To convert Virginia State Plane Coordinates to VDOT Project Coordinates, use the following formula: * Multiply the Easting And Northing Values (For Both Zones) by the Project Specific Combined Scale Factor. (Located above left) * Reverse this Procedure to convert VDOT Project Coordinates (2014) to NAD 83 - U.S. Survey Feet

From Mile Marker 32, 21.0' North From Edge Of Pavement.



Pavement, 3.0' North From Top Of Bank.

VDOT Project Coordinates (2014) East (X): <u>N/A</u> ft. North (Y): <u>N/A</u> ft. Elevation: <u>N/A</u> ft.	VA State Plane Coordinates: NAD 83-U.S. Survey Feb. East (X): 10538542,760 ft. North (Y): 3461979,205 ft. Ortho. Elevation (H): 2028,01 ft. Zone: North South X (place an 'X' beside one)
Project Specific Combined Scale Factor: I. <u>000000000</u> (9 Decimal Places)	Project Information Project Number : <u>PEI2-96I-188, PIOI</u>
Latitude : 36° 47′ [1.58028" N (5 Decimal Places) Longitude : 81° 43′ 31.60173" W (5 Decimal Places)	Route: <u>I-8I (NBL)</u> City/County: <u>Washington</u> Established By: <u>Woolpert</u>
Geoid Separation (N): $\underline{-101,47}$ Ellipsoid Height (h): $\underline{1926,532}$ Horizontal Datum: $\underline{NAD83}$ Year: $\underline{2011-2010,00}$	To convert Virginia State Plane Coordinates to VDOT Project Coordinates, use the following formula:
Vertical Datum: $NAVD88$ Geoid: $I2B$ Azimuth to Station: 904 is $80^{\circ}57'14''$	* Multiply the Easting And Northing Values (For Both Zones) by the Project Specific Combined Scale Factor (Located above left)
Control Based On: OPUS Project <u>CORS Stations VABG, WVAT, LSO4, NCSR</u>	* Reverse this Procedure to convert VDOT Project Coordinates (2014) to NAD 83 - U.S. Survey Feet
-8 SBL -8 SBL -8 NB	23.6' Culvert Sign
	Ground Approx. 0.6 mi. East From Overpass m Edge Of Pavement, 24.7' Southwest

Virginia Department of Transportation Horizontal Control

Control Station 1.D.: <u>903</u> Date: <u>II-19-2019</u>

Control Station I.D.: <u>9C</u>	<u> Date : 11-19-2019</u>
VDOT Project Coordinates (2014) East (X): <u>N/A</u> ft. North (Y): <u>N/A</u> ft. Elevation: <u>N/A</u> ft.	VA State Plane Coordinates: NAD 83- U.S. Survey For East (X): 10543333.801 ft. North (Y): 3462523.908 ft. Ortho. Elevation (H): 2062.87 ft. Zone: North South X (place an 'X' beside one)
Project Specific Combined Scale Factor: I. <u>000000000</u> (9 Decimal Places)	Project Information Project Number : <u>PEI2-96I-I88, PIOI</u>
Latitude: 36° 47′ 18.577.24" N (5 Decimal Places) Longitude: 81° 42′ 32.966.29" W (5 Decimal Places) Geoid Separation (N): -101.47 Ellipsoid Height (h): 1961.40 Horizontal Datum: NAD83 Year: 2011-2010.00 Vertical Datum: NAVD88 Geoid: 12B Azimuth to Station: 905 is 280° 05′ 28" Control Based On: OPUS Project CORS Stations VABG, WVAT, LSO4, NCSR	Route: I-81 (NBL) City/County: Washington Established By: Woolpert To convert Virginia State Plane Coordinates to VD07 Project Coordinates, use the following formula: * Multiply the Easting And Northing Values (For Both Zones) by the Project Specific Combined Scale Facto (Located above left) * Reverse this Procedure to convert VD07 Project Coordinates (2014) to NAD 83 - U.S. Survey Feet
DETAILED SKET	CH (Not to Scale)
	,
1-81 SBL	


1-81 NBL

Pavement, 47.1' North From R/W Fence.

Station Is A Pin W/Cap Set Flush With The Ground Approx. I.6 mi. East From Overpass Of Fleet Rd. & I-81. Station Is 67.2' East From End Of Guardrail, 3.8' South From Edge Of

R/W Fence

LD-200 (REV. 10/2014)



Station Is A Pin W/Cap Set Flush With The Ground Approx. 0.2 mi. West From Overpass Of Fleet Rd. & I-81. Station Is 0.3' South From Edge Of Pavement, 83.6' Southwest From Mile Marker 31.8, 6.9' Northwest From Retaining Wall.

LD-200 (REV. 10/2014)

PROJECT MANAGER <u>James Jones, L.S. (276) 696-3257 (Bristol)</u> SURVEYED BY, DATE <u>Woolpert Inc., (757) 549-3549 (Nov. 24, 2019)</u>

DESIGN BY <u>Tamara_Pritchard.P.E.(276) 696-3249 (Bristol)</u>
SUBSURFACE UTILITY BY, DATE <u>Woolpert_Inc.,(757) 549-3549 (Nov.24.2019)</u>

PH PLANS

THESE PLANS ARE UNFINISHED AND UNAPPROVED AND ARE NOT TO BE USED FOR ANY TYPE OF CONSTRUCTION OR THE ACQUISITION OF RIGHT OF WAY.

SURVEY ALIGNMENT DATA SHEET

	ransportation Horizontal Control 907 Date : <u>II-19</u> -2019
VDOT Project Coordinates (2014) East (X): <u>N/A</u> ft. North (Y): <u>N/A</u> ft. Elevation: <u>N/A</u> ft.	VA State Plane Coordinates: NAD 83-U.S. Survey Feet East (X): <u>10546177.700</u> ft. North (Y): <u>3461492.945</u> ft. Ortho. Elevation (H): <u>1963.13</u> ft. Zone: North South X (place an 'X' beside one)
Project Specific Combined Scale Factor: I. <u>000000000</u> (9 Decimal Places)	Project Information Project Number : <u>PEI2-96I-I88, PI0I</u>
_atitude : <u>36° 47′ 09;34341"</u> N (5 Decimal Places _ongitude : <u>81° 41′ 57;59551"</u> W (5 Decimal Places	Route: <u>I-81 (NBL)</u> City/County: <u>Washington</u>
Geoid Separation (N):- <u>IOI,48</u> Ellipsoid Height (h):1 <u>861.66</u> Horizontal Datum: <u>NAD83</u> Year: <u>2011-2010</u> , Vertical Datum: <u>NAVD88</u> Geoid: <u>12B</u> Azimuth to Station: <u>908</u> is <u>IOO° 34′ 50″</u> Control Based On: OPUS Project CORS Stations VABG,WVAT,LSO4,NCSR	To convert Virginia State Plane Coordinates to VDOT Project Coordinates, use the following formula: * Multiply the Easting And Northing Values (For Both Zones) by the Project Specific Combined Scale Factor. (Located above left) * Reverse this Procedure to convert VDOT Project Coordinates (2014) to NAD 83 - U.S. Survey Feet
DETAILED SK	ETCH (Not to Scale)
 /-8/ SBL 	
1-81 NBL	
Mile Marker 34.1 > 45.7′ Sign > 19.	6.3'

Station Is A Pin W/Cap Set Flush With The Ground Approx. I.3 mi. West From Overpass Of Route 107 & I-81. Station Is 45.7' East From Mile Marker 34.1, 6.3' South From Edge Of

LD-200 (REV. 10/2014)


Pavement, 19.6' Northeast From A Sign.

LD-200 (REV. 10/2014) Virginia Department of Trans Control Station 1.D.: 908	
VDOT Project Coordinates (2014) East (X): <u>N/A</u> ft. North (Y): <u>N/A</u> ft. Elevation: <u>N/A</u> ft.	VA State Plane Coordinates: NAD 83-U.S. Survey Feet East (X): 10546847.910 ft. North (Y): 3461367.754 ft. Ortho. Elevation (H): 1958.23 ft. Zone: North South X (place an 'X' beside one)
Project Specific Combined Scale Factor: I.000000000 (9 Decimal Places) Latitude: 36° 47′ 08.33072" N (5 Decimal Places) Longitude: 81° 41′ 49.30919" W (5 Decimal Places) Geoid Separation (N): -101.48 Ellipsoid Height (h): 1856.75 Horizontal Datum: NAD83 Year: 2011-2010.00 Vertical Datum: NAVD88 Geoid: 128 Azimuth to Station: 907 is 280° 34′ 50" Control Based On: OPUS Project CORS Stations VABG, WVAT, LS04, NCSR	Project Information Project Number: PE12-961-188, P101 Route: 1-81 (NBL) City/County: Washington Established By: Woolpert To convert Virginia State Plane Coordinates to VDOT Project Coordinates, use the following formula: * Multiply the Easting And Northing Values (For Both Zones) by the Project Specific Combined Scale Factor. (Located above left) * Reverse this Procedure to convert VDOT Project Coordinates (2014) to NAD 83 - U.S. Survey Feet CH (Not to Scale)
 /-8/ SBL	
 /-8/ NBL	
Sign № 49.4′	12.0'
Station Is A Pin W/Cap Set Flush With The Grand Of Route 107 & I-81. Station Is 49.4' East From Pavement, 12.0' North From End Of Guardrail.	

Point	Station	Distance	Bearing	Project C	oordinates	Elev.	Desc.
				North (Y)	East (X)		
CSS	901			3460249.009	10534670.036	1974.17	Pin & Cap
		617.76'	N68°44'50E				
CSS	902			3460472.938	10535245.787	1967.03	Pin & Cap
		691.61'	N60°13'55"E				
CSS	717			3460816.317	10535846.136	1958.22	Pin & Cap
		700.42'	N59°05'57"E				
CSS	718			3461176.020	10536447.133	1966.46	Pin & Cap
		571.11'	N61°31'27"E				
CSS	719			3461448.321	10536949.151	1984.95	Pin & Cap
		510.30'	N65°27'12"E				
CSS	720			3461660.315	10537413.329	1995.82	Pin & Cap
		542.55'	N70°56'33"E				<u> </u>
CSS	721			3461837.469	10537926.146	2009.75	Pin & Cap
		632.69'	N77°03'17"E				<u> </u>
CSS	903			3461979.205	10538542.760	2028.01	Pin & Cap
		605.71'	N80°57'14"E				, e. ep
CSS	904			3462074.441	10539140.939	2047.10	Pin & Cap
		598.13'	N81°10'57"E				· o. op
CSS	722	000.20		3462166.126	10539731.997	2070.79	Pin & Cap
		665.59'	N81°14'45E				7 5. 5
CSS	723			3462267.424	10540389.832	2097.31	Pin & Cap
		713.46'	N80°50'03"E				
CSS	724			3462381.073	10541094.180	2121.75	Pin & Cap
		696.97'	N81°03'26"E				
CSS	725			3462489.416	10541782.676	2119.36	Pin & Cap
		547.03'	N83°39'44"E				
CSS	726			3462549.802	10542326.365	2100.20	Pin & Cap
		363.54'	N88°17'29"E				
CS	905			3462560.641	10542689.740	2086.52	Pin & Cap
		645.11'	S86°44'09"E				
CS	906			3462523.908	10543333.801	2062.87	Pin & Cap
		710.89'	S79°54'32"E				1
CS	727			3462399.352	10544033.691	2036.44	Pin & Cap
		681.00'	S72°42'32"E				
CS	728			3462196.939	10544683.919	2010.45	Pin & Cap
		785.80'	S65°09'23"E				 -
CS	729			3461866.791	10545396.997	1984.41	Pin & Cap
		865.60'	S64°24'44"E				
CS	907	1.2.2		3461492.945	10546177.700	1963.13	Pin & Cap
-		681.80'	S79°25'10"E				
CS	908			3461367.754	10546847.910	1958.23	Pin & Can
-							

3/11/2021 12:10:38 PM

LIMITED ACCESS HIGHWAY By Resolution of Highway Commission dated October 4, 1956



ROUTE

VA. | 81

DESIGN FEATURES RELATING TO CONSTRUCTION OR TO REGULATION AND CONTROL OF TRAFFIC MAY BE SUBJECT TO CHANGE AS DEEMED

NECESSARY BY THE DEPARTMENT

REVISED

LIMITED ACCESS HIGHWAY

By Resolution of Highway Commission dated October 4, 1956

PROJECT

0081-095-829, RW-201

C-50i

PROJECT MANAGER *James Jones,L.S. (276) 696-3257 (Bristol)* SURVEYED BY, DATE _*Woolpert_Inc., (757)_549-3549_(Nov.24,2019)*_______ DESIGN BY *Tamara Pritchard, P.E.* (276) 696-3249 (*Bristol*) , SUBSURFACE UTILITY BY, DATE <u>Woolpert Inc., (757) 549-3549 (Nov.24,2019)</u>

TRANSPORTATION MANAGEMENT PLAN

- I.) PROJECT CATEGORY (MINIMUM TMP REQUIREMENTS)
- A.) THIS WILL BE A TYPE B.CATEGORY III PROJECT.
- B.) THE LENGTH OF THE WORK ZONE WILL BE 6,659 FEET. THE WIDTH OF THE WORK ZONE WILL VARY 4 FEET TO 170 FEET.
- C.) ALLOWABLE WORK ZONE HOURS SHALL BE IN ACCORDANCE WITH THE LMITATIONS OF OPERATIONS SPECIAL PROVISION AND SHEET 1J(2).
- D.) THE TRAFFIC IN THIS AREA CONSIST OF PRIMARILY LOCAL TRAFFIC, COMMUTERS, AND TRUCK TRAFFIC.
- E.) ALL NORTHBOUND TRAVEL LANES AND SHOULDERS WILL BE AFFECTED BY THE PROJECT WORK.
- F.) SPEED LIMIT OF ROADWAY IS REDUCED TO 60 MPH (NORMAL SPEED LIMIT IS 70 MPH.
- 2.) TEMPORARY TRAFFIC CONTROL (TTC) PLAN: (COMPONENT I)
- A.) MAJOR COMPONENTS WILL CONSIST OF GENERAL NOTES AND SPECIAL DETAILS.
- B.) SPECIFIC TRAFFIC CONTROL FIGURES AND NOTES FROM THE 2001VA WAPM.REVISION 2 -2019 USED FOR TRAFFIC CONTROL ARE: TTC-IJ - WORK BEYOND THE SHOULDER OPERATION TTC-7.J - SHOULDER CLOSURE WITH BARRIER AND LANE SHIFT OPERATION TTC-16.2 - OUTSIDE LANE CLOSURE OPERATION ON A FOUR-LANE ROADWAY TTC-17.2 - INSIDE LANE CLOSURE OPERATION ON A FOUR-LANE ROADWAY TTC-39.2 - WORK OPERATION IN THE VICINITY OF AN ENTRANCE RAMP
 - TTC-52.2 SIGNING FOR SPEED LIMIT AND FINE SIGNS IN WORK ZONES TTC-53.0 - SIGNING FOR PROJECT LIMITS
- TTC-55, ERADICATION OF PAVEMENT MARKINGS IN A WORK ZONE TTC-60.0 - TEMPORARY PAVEMENT MARKING AND MARKER GUIDELINES
- 3.) PUBLIC COMMUNICATION STRATEGIES: (COMPONENT 2)
- A.) PROJECT DESCRIPTION

THE PROJECT WILL INCLUDE WIDENING OF 1-81 NB TO ACCOMODATE THE ADDITION OF A TRUCK CLIMBING LANE.

- B.) TRAFFIC IMPACTS
 - I-81 NB: TEMPORARY LANE CLOSURES AND SHOULDER CLOSURES
- C.) THE CONTRACTOR SHALL NOTIFY THE DISTRICT COMMUNICATIONS OFFICE AT (276) 696-3283 AT LEAST 72 HOURS IN ADVANCE OF ANY SCHEDULED WORK PLANS THAT WILL CAUSE TRAFFIC DELAYS OR CHANGES TO TRAFFIC PATTERNS.
- D.) THE CONTRACTOR SHALL NOTIFY THE REGIONAL TRANSPORTATION OPERATIONS CENTER AT (540) 375-0170 IN ACCORDANCE WITH THE TECHNICAL REQUIREMENTS TO PLACE LANE CLOSURE INFORMATION ON THE 511 SYSTEM AND VA-TRAFFIC.
- 4.) TRAFFIC OPERATIONS (TO) PLAN
- A.) TRAFFIC BACKUP NOTIFICATION

EMERGENCY CONTACT FOR THIS PROJECT SHALL BE 911.

THE TRAFFIC OPERATIONS CENTER (540) 387-5320 SHALL BE NOTIFIED OF LANE CLOSURES OR OTHER TRAFFIC IMPACTS BY THE PROJECT STAFF. THE TOC WILL UTILIZE AVAILABLE SYSTEMS (CAMERAS, SENSORS, ETC) TO MONITOR THE WORK AREA AND ALL ADJACENT AREAS. THE TOC WILL MAKE ALL ENTRIES INTO SYSTEMS THAT FEED THIS INFORMATION INTO 511.THE TOC WILL UTILIZE ASSETS SUCH AS PERMANENT AND MOBILE VARIABLE MESSAGE SIGNS WITH CDMA MODENS TO ALERT MOTORISTS OF LANE CLOSURES AND OTHER INCIDENTS THAT MAY IMPACT TRAVEL.

THE TOC WILL ALSO MAKE NOTIFICATIONS TO DEPARTMENT STAFF. THE STAFF NOTIFICATIONS SHALL INCLUDE BUT NOT BE LIMITED TO THE DUTY OFFICER, AREA CONSTRUCTION ENGINEER, PROJECT MAINTENANCE OF TRAFFIC COORDINATOR, PROJECT MANAGER, RESIDENT ADMINISTRATOR, DISTRICT WORK ZONE SAFETY COORDINATOR, DISTRICT TRAFFIC ENGINEER, REGIONAL TRAFFIC OPERATIONS MANAGER, REGIONAL INCIDENT MANAGEMENT COORDINATOR, AND DISTRICT COMMUNICATIONS OFFICE MANAGER OF ANY INCIDENTS AND EXPECTED TRAFFIC DELAYS.

THE TOC SHALL BE RESPONSIBLE FOR INTRA-AGENCY NOTIFICATIONS TO ENTITIES SUCH AS, BUT NOT LIMITED TO, WASHINGTON COUNTY ADMINISTRATOR, VIRGINIA STATE POLICE, LOCAL 911, AND OTHER AFFECTED AGENCIES.

A REVIEW OF ALL MAJOR INCIDENTS, AS DETERMINED BY THE REGIONAL INCIDENT MANAGEMENT COORDINATOR, SHALL BE ACCOMPLISHED WITHIN 48 HOURS OF CLEARANCE OF THE INCIDENT. VDOT PROJECT STAFF, REGIONAL OPERATIONS STAFF, CONTRACTOR STAFF, AND EMERGENCY RESPONDERS SHALL BE REPRESENTED AT THESE MEETINGS.

TARGET AUDIENCE	CONTACT METHOD	PHONE NUMBER, E-MAIL OR ADDRESS	RESPONSIBLE CHARGE
MOTORISTS	NEWS RELEASE, WEEKLY TRAFFIC INFORMATION (ROADWATCH) AND TRAFFIC OPERATIONS CENTER	SEE PUBLIC AFFAIRS NEW RELEASE DISTRIBUTION LIST (E-MAIL AND FAX)	DISTRICT COMMUNICATIONS OFFICE MICHELLE EARL (276) 696-3283
POLICE,EMS	PHONE	EMERGENCY: 911 VIRGINIA STATE POLICE (AREA 27 OFFICE): 276-669-2641 WASHINGTON CO.VOLUNTEER FIRE DEPT: 276-669-1411 WASHINGTON CO.EMERGENCY MANAGEMENT: 276-525-1330	ACE BRIAN PLUMMER 276-696-3439
COUNTY/TOWN OFFICIALS	PHONE	WASHINGTON COUNTY ADMINISTRATOR 276-525-1300	ACE BRIAN PLUMMER 276-696-3439
VDOT		REGIONAL TRANSPORTATION OPERATION CENTER (TOC): 540-375-0170 BRISTOL DISTRICT OFFICE: 276-669-6151 DISTRICT COMMUNICATIONS OFFICE: 276-696-3283 ABINGDON RESIDENCY ADMINISTRATOR: 276-676-5503 DISTRICT WORK ZONE SAFETY COORDINATOR: 276-696-3425 AREA CONSTRUCTION ENGINEER: 276-696-3439	

VDOT Traffic

Bristol, Virginia

TRAFFIC ENGINEER

VDOT Location & Design

Bristol, Virginia

ROADWAY ENGINEER

PH PLANS

THESE PLANS ARE UNFINISHED AND UNAPPROVED AND ARE NOT TO BE USED FOR ANY TYPE OF CONSTRUCTION OR THE ACQUISITION OF RIGHT OF WAY.

PROJECT	SHEET NO.
0081-095-829	IJ(I)

81

LIMITED ACCESS HIGHWAY

By Resolution of Highway Commission dated October 4, 1956

REVISED ROUTE PROJECT 0081-095-829, RW-201

C-50i

DESIGN FEATURES RELATING TO CONSTRUCTION OR TO REGULATION AND CONTROL OF TRAFFIC MAY BE SUBJECT TO CHANGE AS DEEMED NECESSARY BY THE DEPARTMENT

VA.

VDOT Traffic VDOT Location & Design Bristol, Virginia Bristol, Virginia ROADWAY ENGINEER TRAFFIC ENGINEER

TRANSPORTATION MANAGEMENT PLAN

GENERAL NOTES

PROJECT MANAGER <u>James Jones, L.S. (276) 696-3257 (Bristol)</u>

SURVEYED BY, DATE *Woolpert Inc.* (757) 549-3549 (Nov.24,2019)

DESIGN BY *Tamara Pritchard, P.E.* (276) 696-3249 (*Bristol*) SUBSURFACE UTILITY BY, DATE Woolpert Inc., (757) 549-3549 (Nov. 24, 2019)

> UNLESS OTHERWISE APPROVED OR DIRECTED BY THE ENGINEER, THE CONTRACTOR SHALL PLAN AND PROSECUTE THE WORK IN ACCORDANCE WITH THIS TRANSPORTATION MANAGEMENT PLAN.

THE NOTES IN THIS TRANSPORTATION PLAN ARE IN ADDITION TO ALL APPLICABLE STANDARDS, SPECIFICATIONS, AND CONTRACT DOCUMENTS. ALL TRAFFIC MAINTENANCE SHALL CONFORM WITH THE FOLLOWING AND THE LATEST REVISIONS THERETO:

2009 MANUAL ON UNIFORM TRAFFIC CONTROL DEVICES (REV.I AND 2) 2011 VIRGINIA SUPPLEMENT TO THE 2009 MUTCD (REV.1) 2011 VIRGINIA WORK AREA PROTECTION MANUAL (REV.2) 2016 VDOT ROAD AND BRIDGE STANDARDS (LATEST REVISION) 2020 VDOT ROAD AND BRIDGE SPECIFICATIONS (LATEST REVISION)

THE TRANSPORTATION MANAGEMENT PLAN (TMP) IS INTENDED AS A GUIDE. IT IS NOT INTENDED TO ENUMERATE EVERY DETAIL WHICH MUST BE CONSIDERED IN THE CONSTRUCTION OF THIS PROJECT.BUT ONLY TO SHOW THE GENERAL HANDLING OF TRAFFIC.IT SHALL BE THE RESPONSIBILITY OF THE CONTRACTOR TO PRESENT A FORMAL TMP/MAINTENANCE OF TRAFFIC (MOT) PLAN TO THE ENGINEER FOR APPROVAL PRIOR TO ANY CONSTRUCTION THAT MAY AFFECT THE EXISTING TRAFFIC.

AT THE CONCLUSION OF EACH WORKDAY, EQUIPMENT SHALL NOT BE STORED WITHIN THE ESTABLISHED CLEAR ZONE AND/OR DEFLECTION ZONE OF PHYSICAL BARRIERS IN ACCORDANCE WITH THE CONTRACT DOCUMENTS. ANY AREAS EXCAVATED BELOW THE EXISTING PAVEMENT SURFACE AND WITHIN THE CLEAR ZONE, SHALL BE BACKFILLED WITH APPROVED MATERIAL TO FORM AN APPROXIMATE 6: WEDGE AGAINST THE EXISTING PAVEMENT SURFACE FOR THE SAFETY AND PROTECTION OF VEHICULAR TRAFFIC. SEE TEMPORARY WEDGE DETAIL ON VDOT STD. ACOT-I IN THE 2016 ROAD AND BRIDGE STANDARDS. SEE APPENDIX A OF THE VAWAPM FOR DROP-OFF REQUIREMENTS.

ALL SIGNS, GROUP 2 CHANNELIZING DEVICES, AND ANY OTHER DEVICES USED IN THE CONSTRUCTION ZONE SHALL BE FURNISHED BY THE CONTRACTOR AND SHALL BE KEPT CLEAN AND PROPERLY ALIGNED AT ALL TIMES.

THE INSTALLATION AND REMOVAL OF GUARDRAIL SHALL BE COORDINATED SO AS NOT TO PRESENT ANY BLUNT END OR HAZARD TO THE MOTORING PUBLIC.

WHEN UTILIZED, TRAFFIC BARRIER SERVICE SHALL BE INSTALLED AND REMOVED SO AS NOT TO PRESENT ANY BLUNT END OR HAZARD TO THE MOTORING PUBLIC. THE PLACEMENT AND REMOVAL OF THE TRAFFIC BARRIER SERVICE AND BARRICADES ARE TO BE COORDINATED BY THE PROJECT SAFETY OFFICER.

THE CONTRACTOR SHALL MAINTAIN ALL SIGNAGE WITHIN THE LIMITS OF CONSTRUCTION. SHOWN OR OTHERWISE. UNLESS DIRECTED BY THE ENGINEER. IF REMOVAL IS ALLOWED, CONTRACTOR SHALL STORE THE SIGNS PER VDOT STANDARDS, AND IF DIRECTED, REPLACE THEM AT THE COMPLETION OF THE PROJECT.

THE CONTRACTOR SHALL ENSURE POSITIVE DRAINAGE FOR THE DURATION OF THE PROJECT. ADDITIONAL TEMPORARY MEASURES MAY BE NEEDED TO FACILITATE PROPER POSITIVE DRAINAGE.

THE CONTRACTOR SHALL SCHEDULE ALL PHASES OF CONSTRUCTION IN SUCH A MANNER THAT WATER, SEWER, CABLE, POWER, AND ANY OVERHANGING OR UNDERGROUND UTILITY SERVICES WILL NOT BE INTERRUPTED. THE CONTRACTOR SHALL COORDINATE THEIR UTILITY ADJUSTMENTS/RELOCATION ACTIVITIES WITH THE OWNER OF THE UTILITY.

EROSION AND SEDIMENT CONTROL MEASURES SHALL BE IN PLACE PRIOR TO THE BEGINNING OF CONSTRUCTION, AND SHALL BE REVISED AS NEEDED THROUGH CONSTRUCTION PHASES.

THE CONTRACTOR IS RESPONSIBLE FOR COORDINATING THE CONSTRUCTION. SIGNING, AND TRAFFIC MANAGEMENT PLAN WITH OTHER ADJACENT PROJECTS UNDER CONSTRUCTION.

THE CONTRACTOR SHALL SUBMIT TRAFFIC CONTROL PLANS NOT EXPRESSLY OUTLINED IN THE VAWAPM FOR APPROVAL PRIOR TO PERFORMING THE WORK, NO DEVIATIONS FROM THE PLANS WILL BE ALLOWED WITHOUT PRIOR APPROVAL FROM THE ENGINEER.

UNDER NO CIRCUMSTANCES SHALL CONCURRENT CONSTRUCTION LEFT AND RIGHT OF ANY LANE BE ALLOWED, UNLESS DIRECTED BY THE VDOT PROJECT MANAGER.

MEASURES SHALL BE TAKEN TO ENSURE ADEQUATE SIGHT DISTANCES DURING CONSTRUCTION OPERATIONS.TRAFFIC CONTROL DEVICES.SIGNS.CONSTRUCTION EQUIPMENT, MATERIAL STORAGE, OR ANY OTHER OBSTACLE WILL NOT BE ALLOWED TO INTERFERE WITH HORIZONTAL OR VERTICAL SIGHT DISTANCES.

GENERAL NOTES (CONT.)

ACCESS INTO AND OUT OF THE WORK ZONE SHALL TAKE INTO ACCOUNT ADEQUATE SIGHT DISTANCE AND ACCELERATION AND DECELERATION LENGTHS FOR CONSTRUCTION VEHICLES AND EQUIPMENT.INGRESS/EGRESS SHALL BE IN ACCORDANCE WITH THE VIRGINIA WORK AREA PROTECTION MANUAL.

EXISTING CONFLICTING PAVEMENT MARKINGS SHALL BE COMPLETELY ERADICATED BY GRINDING OR COVERED WITH TYPE E CONSTRUCTION MARKINGS.

THE CONTRACTOR SHALL TEMPORARILY COVER ANY EXISTING SIGNS THAT ARE CONTRARY TO CONSTRUCTION SIGNS AND UNCOVER THESE AT THE COMPLETION OF THE PROJECT AS DIRECTED BY THE ENGINEER.

CHANNELIZING DEVICE SPACING: TRANSITION: 40-FT TRAVELWAY: 80-FT

LANE/SHOULDER CLOSURES NEEDED

I. SINGLE LANE CLOSURES IN ACCORDANCE WITH VA WAPM TTC-16.2 AND 17.2 2. SHOULDER CLOSURES AS SHOWN IN PLAN AND IN ACCORDANCE WITH VA WAPM

ALLOWABLE LANE CLOSURE HOURS:

	Bristol District Interstate Allowable Work Hours									
Single Lane Closu	ıre									
				Recommended A Labor Day thro			Recommeneded Allowal Memorial Day through			
					Hours	Hours		Hours	Hours Available	
Roadway	Counties	Location	Direction	Sunday Night thru Friday Morning	Available per night	Available per week	Sunday Night thru Friday Morning	Available per night	per week	Comments
I-81	Washington & Smyth	MP 23 to MP 43	NB & SB	7 PM to 6 AM	11	55	7 PM to 6 AM	11	55	
Shoulder Closure										
				Recommended A	llowable W	orkhours				
Roadway	Counties	Location	Direction	Sunday Night thru Friday Morning	Hours Available per day	Hours Available per week	Comments			
I-81	Washington & Smyth	MP 23 to MP 43	NB & SB	12 AM to 12AM	24	120	7 PM Sunday to 6 AM Friday			

THESE ALLOWABLE HOURS SHALL BE APPLICABLE UNLESS OTHERWISE APPROVED BY THE ENGINEER.

IN ADDITION TO THE WORK RESTRICTIONS FOR HOLIDAYS IN PART 5, SECTION 108.02 (LIMITATION OF OPERATIONS), THE FOLLOWING HOLIDAYS AND EVENTS SHALL BE SUBJECT TO SAME RESTRICTIONS:

BRISTOL SPRING AND FALL NASCAR RACE

PORTABLE CHANGEABLE MESSAGE SIGNS

PORTABLE CHANGEABLE MESSAGE SIGNS (PCMS) SHALL BE USED IN ADVANCE OF THE WORK ZONE IN ACCORDANCE WITH THE CONTRACT.

PH PLANS

THESE PLANS ARE UNFINISHED AND UNAPPROVED AND ARE NOT TO BE USED FOR ANY TYPE OF CONSTRUCTION OR THE ACQUISITION OF RIGHT OF WAY.

> SHEET NO. **PROJECT** IJ(2) 0081-095-829

PROJECT MANAGER *James Jones.L.S. (276) 696-3257 (Bristol)* SURVEYED BY, DATE <u>Woolpert Inc., (757) 549-3549 (Nov.24,2019)</u> DESIGN BY *Tamara Pritchard, P.E.* (276) 696-3249 (Bristol) SUBSURFACE UTILITY BY, DATE Woolpert Inc., (757) 549-3549 (Nov. 24, 2019)

INCIDENT MANAGEMENT NOTES:

I.THE CONTRACTOR SHALL BE RESPONSIBLE FOR IMPLEMENTING AND PROVIDING THE FOLLOWING:

NOTIFY THE VDOT PROJECT MANAGER & THE REGIONAL TRANSPORTATION OPERATIONS CENTER (TOC) IN ACCORDANCE WITH THE TECHNICAL REQUIREMENTS TO PLACE LANE CLOSURE INFORMATION ON THE 511 SYSTEM AND VA-TRAFFIC. THE TELEPHONE NUMBER TO THE TOC IS 540-375-0170.

PROVIDE ALL FIELD CREW A LIST OF EMERGENCY RESPONSE AGENCIES INCLUDING:

POLICE/AMBULANCE/FIRE/SAFETY/HAZMAT SPILLS - 911 VIRGINIA STATE POLICE - 276.669.2641 WASHINGTON CO.SHERIFF - 276.676.6000

WASHINGTON CO.EMERGENCY MANAGEMENT - 276.525.1330

PROCEDURES TO RESPOND TO TRAFFIC INCIDENTS THAT OCCUR IN THE WORK ZONE:

I. THE CONTRACTOR IS REQUIRED TO IMMEDIATELY REPORT TO THE STATE POLICE AND THE VDOT PROJECT MANAGER.

2. THE CONTRACTOR SHALL ASSIST IN PROVIDING EMERGENCY RESPONDERS ACCESS TO THE INCIDENT (AS NECESSARY).

3. THE CONTRACTOR SHALL NOTIFY THE TOC WHICH WILL SET INTO PLACE THE PROCEDURE DEFINED FOR UNSCHEDULED TRAFFIC BACKUP/DELAY.

4. UPON NOTIFICATION FROM THE TOC OF AN INCIDENT REQURING A DETOUR. THE CONTRACTOR SHALL ESTABLISH THE DETOUR WITHIN ONE (I) HOUR FROM 5 AM-9 PM DAILY.THE CONTRACTOR SHALL ESTABLISH THE DETOUR WITHIN TWO (2) HOURS DURING ALL OTHER TIMES NOT REFERENCED.

5. DEPENDING ON THE SEVERITY OF THE INCIDENT, THE CONTRACTOR MAY HAVE TO SHUT DOWN WORK ZONES.

6. UPON ARRIVAL ON THE SCENE, THE VIRGINIA STATE POLICE WILL DETERMINE RESPONSE NECESSARY TO ALL TRAVELING PUBLIC AROUND THE INCIDENT.

7. TOC SHALL NOTIFY DISTRICT COMMUNICATIONS OFFICE AND THE RESIDENCY OFFICE OF THE INCIDENT.

8. THE CONTRACTOR SHALL COMPLETE AN ACCIDENT REPORT TO INCLUDE SKETCHES AND PHOTOS OF THE WORK ZONE. THE VIRGINIA STATE POLICE WILL TAKE CONTROL OF THE INCIDENT AND DIRECT ITS CLEARING AND RESTORATION TO NORMAL TRAFFIC

9. THE VIRGINIA STATE POLICE REPORT OF THE INCIDENT WILL BE REVIEWED BY THE AREA CONSTRUCTION ENGINEER TO DETERMINE IF ANY MODIFICATION OF THE TEMPORARY TRAFFIC CONTROL PLAN IS NECESSARY. IF IT IS DETERMINED THAT IT IS NECESSARY TO ALTER THE PLAN, A MEETING WILL BE CALLED WITH THE CONTRACTOR, VDOT PROJECT PERSONNEL, VDOT SAFETY REPRESENTATIVES, AND THE VIRGINIA STATE POLICE (IF NECESSARY) TO DISCUSS MODIFICATION AND IMPLEMENTATION OF AN IMPROVED TRAFFIC CONTROL PLAN.

10. WITHIN 24 HOURS OF ANY INCIDENTS WITHIN THE CONSTRUCTION WORK ZONE, A REVIEW OF THE TRAFFIC CONTROLS SHALL BE COMPLETED AND NECESSARY ADJUSTMENTS MADE TO REDUCE THE POTENTIAL FOR FUTURE INCIDENTS.

DETOUR NOTES:

I. DETOUR MAP SHOWN MODELED AFTER VA WAPM TIMC-8.J. 2. WHEN INCIDENT ON I-81 REQUIRES CLOSURE OF NORTHBOUND LANES THROUGH THE WORK ZONE, ADDITIONAL SIGNING IN ACCORDANCE WITH VA WAPM TIMC-7.1 MAY BE NECESSARY.

3. DURING AN INCIDENT, ADVANCE PORTABLE CHANGEABLE MESSAGE SIGNS (PCMS) SHALL DISPLAY RELEVANT INFORMATION CONCERNING THE INCIDENT. THE FOLLOWING MESSAGES ARE SUGGESTED:


A. IN THE EVENT THE INTERSTATE IS CLOSED:


SCREEN I <u>SCREEN 2</u> ALL VEH *NORTH* MUST CLOSED EXIT


B. IN THE EVENT THE INTERSTATE IS STILL OPEN:

SCREEN I <u>SCREEN 2</u> EXPECT AHEAD **DELAYS**

TRANSPORTATION MANAGEMENT PLAN







PH PLANS

THESE PLANS ARE UNFINISHED AND UNAPPROVED AND ARE NOT TO BE USED FOR ANY TYPE OF CONSTRUCTION OR THE ACQUISITION OF RIGHT OF WAY.

NOT TO SCALE 0081-095-829 SHEET NO.

LEGEND:

DENOTES PROPOSED DETOUR ROUTE

I IMITED ACCESS HIGHWAY By Resolution of Highway Commission

PROJECT MANAGER *James Jones,L.S. (276) 696-3257 (Bristol)* SURVEYED BY, DATE *Woolpert Inc.* (757) 549-3549 (Nov.24,2019) DESIGN BY Tamara Pritchard, P.E. (276) 696-3249 (Bristol) SUBSURFACE UTILITY BY, DATE <u>Woolpert Inc., (757) 549-3549 (Nov.24,2019)</u>

PH PLANS

THESE PLANS ARE UNFINISHED AND UNAPPROVED AND ARE NOT TO BE USED FOR ANY TYPE OF CONSTRUCTION OR THE ACQUISITION OF RIGHT OF WAY.

TRANSPORTATION MANAGEMENT PLAN SEQUENCE OF CONSTRUCTION

SEQUENCE OF CONSTRUCTION

PHASE I

- I. MEDIAN SHOULDER STRENGTHENING SHALL BE CONSTRUCTED UNDER PROJECT NO. 0081-961-642, P-101, N-501 (UPC 116723) PRIOR TO CONSTRUCTION OF THIS PROJECT.
- 2. THE CONTRACTOR SHALL SUBMIT NEW MATERIALS AND ITEMS REQUIRED TO COMPLETE THE REMOVAL OR MODIFICATIONS OF EXISTING ITEMS TO THE ENGINEER FOR REVIEW AND APPROVAL IN ACCORDANCE WITH SECTION 105 OF VDOT SPECIFICATIONS.
- 3. INSTALL CONSTRUCTION SIGNS TO COINCIDE WITH CONSTRUCTION ACTIVITIES.
- 4. INSTALL PERIMETER E&S CONTROLS AS SHOWN IN THE PLANS.
- 5. TEMPORARILY CLOSE THE NORTHBOUND INSIDE LANE IN ACCORDANCE WITH VA WAPM TTC-17.2 (INSIDE LANE CLOSURE OPERATION ON A FOUR-LANE ROADWAY).
- 6. PERFOM FLEXIBLE PLANING AND OVERLAY ON THE INSIDE SHOULDER TO REMOVE AND RELOCATE RUMBLE STRIPS.

PHASE 2

- INSTALL CONSTRUCTION SIGNS TO COINCIDE WITH CONSTRUCTION ACTIVITIES.
- 2. TEMPORARILY CLOSE THE NORTHBOUND OUTSIDE LANE IN ACCORDANCE WITH VA WAPM TTC-16.2 (OUTSIDE LANE CLOSURE OPERATION ON A FOUR-LANE ROADWAY).
- 3. INSTALL TRAFFIC BARRIER SERVICE ADJACENT TO THE OUTSIDE SHOULDER AS SHOWN IN MOT PLAN (MODELED AFTER TTC-7,1 - SHOULDER CLOSURE WITH BARRIER AND LANE SHIFT OPERATION). AFTER INSTALLATION, RE-OPEN TWO LANES OF TRAFFIC.
- 4. INSTALL PERIMETER E&S CONTROLS AS SHOWN IN THE PLANS.
- 5. INSTALL ACCESS AREAS AS NEEDED.
- 6. CONSTRUCT ROADWAY WIDENING.
- 7. TEMPORARILY CLOSE NORTHBOUND OUTSIDE LANE IN ACCORDANCE WITH VA WAPM TTC-16.2 (OUTSIDE LANE CLOSURE OPERATION ON A FOUR-LANE ROADWAY).
- 8. REMOVE TRAFFIC BARRIER SERVICE.

PHASE 3

- I. TEMPORARILY CLOSE NORTHBOUND OUTSIDE AND INSIDELANES SEPARATELY IN ACCORDANCE WITH VA WAPM TTC-16.2/TTC-17.2 (OUTSIDE & INSIDE LANE CLOSURE OPERATION ON A FOUR-LANE ROADWAY.
- 2. COMPLETE FINAL SURFACE PAVING ALONG 1-81 NB.
- 3. COMPLETE FINAL PAVEMENT MARKINGS ALONG 1-81 NB.


		LIMITED AC	/CE22 F	HIGHWA	dated October 4, 1956	
		REVISED	STATE		STATE	SHEET N
			SIAIE	ROUTE	PROJECT	SHEET IN
			VA.	81	0081-095-829, RW-201 C-501	IJ(4,
			ATION AND ECT TO C) CONTRI HANGE A		
VDOT Traffic Bristol, Virginia TRAFFIC ENGINEER	VDOT Location & Design Bristol, Virginia ROADWAY ENGINEER					

0081-095-829

PROJECT MANAGER *James Jones,L.S. (276) 696-3257 (Bristol)* SURVEYED BY, DATE _*Woolpert Inc., (757) 549-3549 (Nov.24,2019)*_____

DESIGN BY Tamara Pritchard, P.E. (276) 696-3249 (Bristol)

SUBSURFACE UTILITY BY, DATE Woolpert Inc., (757) 549-3549 (Nov. 24, 2019)





VDOT Traffic	VDOT Location & Design

Bristol, Virginia

ROADWAY ENGINEER


3 TYPE A 6"YELLOW SOLID

4 TYPE A 8" YELLOW SOLID

ONE-WAY TEMPORARY PAVEMENT MARKERS SHALL BE INSTALLED ON 20'CENTERS ON LANE SHIFT TAPERS

Bristol, Virginia


TRAFFIC ENGINEER



DESIGN FEATURES RELATING TO CONSTRUCTION OR TO REGULATION AND CONTROL OF TRAFFIC MAY BE SUBJECT TO CHANGE AS DEEMED NECESSARY BY THE DEPARTMENT

PH PLANS

THESE PLANS ARE UNFINISHED AND UNAPPROVED AND ARE NOT TO BE USED FOR ANY TYPE OF CONSTRUCTION OR THE ACQUISITION OF RIGHT OF WAY.



MAINTENANCE OF TRAFFIC LEGEND

AREA UNDER CONSTRUCTION (THIS PHASE)

AREA PREVIOUSLY CONSTRUCTED

5 TRAFFIC BARRIER SERVICE CONCRETE, ST'D. MB-IIA


- 6 GROUP 2 CHANNELIZING DEVICE
- **■** CONSTRUCTION SIGN
- GROUP 2 CHANNELIZING DEVICE
- ← TRAFFIC FLOW ARROW
- ── IMPACT ATTENUATOR, TYPE 1, TL-3
- * TYPE B WARNING LIGHT
- SHADOW VEHICLE WITH TMA


0081-095-829

0081-095-829

LIMITED ACCESS HIGHWAY

By Resolution of Highway Commission dated October 4, 1956 ROJECT MANAGER *James Jones, L.S. (276) 696-3257 (Bristol)* SURVEYED BY, DATE _*Woolpert Inc., (757) 549-3549 (Nov.24,2019)*_____ PROJECT ROUTE DESIGN BY Tamara Pritchard, P.E. (276) 696-3249 (Bristol) MAINTENANCE OF TRAFFIC = SUBSURFACE UTILITY BY, DATE Woolpert Inc., (757) 549-3549 (Nov. 24, 2019) 0081-095-829, RW-201 VA. 81 SEQUENCE OF CONSTRUCTION DESIGN FEATURES RELATING TO CONSTRUCTION OR TO REGULATION AND CONTROL OF TRAFFIC MAY BE SUBJECT TO CHANGE AS DEEMED PHASE 1 NECESSARY BY THE DEPARTMENT VDOT Traffic VDOT Location & Design PH PLANS Bristol, Virginia Bristol, Virginia ROADWAY ENGINEER TRAFFIC ENGINEER THESE PLANS ARE UNFINISHED AND UNAPPROVED AND ARE NOT TO BE USED FOR ANY TYPE OF CONSTRUCTION OR THE ACQUISITION OF RIGHT OF WAY. \mathcal{E} 730' - 760' BUFFER 111 5 MILL & OVERLAY SHOULDER AND REMOVE — AND RELOCATE RUMBLE STRIPS **PREVIOUSLY** ST ABILIZED -SH0ULDER MAINTENANCE OF TRAFFIC LEGEND AREA UNDER CONSTRUCTION (THIS PHASE) ST'D.RS-I REO'D. AREA PREVIOUSLY CONSTRUCTED 5 TRAFFIC BARRIER SERVICE CONCRETE, ST'D. MB-IIA 6 GROUP 2 CHANNELIZING DEVICE TEMPORARY PAVEMENT MARKING • CONSTRUCTION SIGN ① TYPE A 6" WHITE SOLID • GROUP 2 CHANNELIZING DEVICE ② TYPE A 8" WHITE SOLID ← TRAFFIC FLOW ARROW 3 TYPE A 6"YELLOW SOLID ── IMPACT ATTENUATOR, TYPE 1, TL-3 4 TYPE A 8"YELLOW SOLID ONE-WAY TEMPORARY PAVEMENT MARKERS SHALL BE INSTALLED ON 20'CENTERS ON LANE SHIFT TAPERS * TYPE B WARNING LIGHT SHADOW VEHICLE WITH TMA SHEET NO. MAINTENANCE OF TRAFFIC = SEQUENCE OF CONSTRUCTION PHASE 1






DESIGN FEATURES RELATING TO CONSTRUCTION OR TO REGULATION AND CONTROL OF TRAFFIC MAY BE SUBJECT TO CHANGE AS DEEMED NECESSARY BY THE DEPARTMENT

PH PLANS

THESE PLANS ARE UNFINISHED AND UNAPPROVED AND ARE NOT TO BE USED FOR ANY TYPE OF CONSTRUCTION OR THE ACQUISITION OF RIGHT OF WAY.



MILL & OVERLAY SHOULDER AND REMOVE — AND RELOCATE RUMBLE STRIPS

STABILIZED

ST'D.RS-I REQ'D.

SHOULDER

MAINTENANCE OF TRAFFIC LEGEND

AREA UNDER CONSTRUCTION (THIS PHASE)

AREA PREVIOUSLY CONSTRUCTED

(5) TRAFFIC BARRIER SERVICE CONCRETE, ST'D. MB-IIA

6 GROUP 2 CHANNELIZING DEVICE • CONSTRUCTION SIGN

TEMPORARY PAVEMENT MARKING

() TYPE A 6" WHITE SOLID

② TYPE A 8" WHITE SOLID

3 TYPE A 6"YELLOW SOLID

4 TYPE A 8" YELLOW SOLID

ONE-WAY TEMPORARY PAVEMENT MARKERS SHALL BE INSTALLED ON 20'CENTERS ON LANE SHIFT TAPERS

• GROUP 2 CHANNELIZING DEVICE

← TRAFFIC FLOW ARROW

── IMPACT ATTENUATOR, TYPE 1, TL-3

₩ TYPE B WARNING LIGHT

SHADOW VEHICLE WITH TMA

PROJECT SHEET NO. 0081-095-829

MILL & OVERLAY SHOULDER AND REMOVE -AND RELOCATE RUMBLE STRIPS

> PREVIOUSLY ST ABILIZED -

SH0ULDER

ST'D.RS-I REQ'D.-

MAINTENANCE OF TRAFFIC LEGEND

AREA PREVIOUSLY CONSTRUCTED

(5) TRAFFIC BARRIER SERVICE CONCRETE, ST'D. MB-IIA

• CONSTRUCTION SIGN

← TRAFFIC FLOW ARROW

* TYPE B WARNING LIGHT

SHADOW VEHICLE WITH TMA

TEMPORARY PAVEMENT MARKING

() TYPE A 6" WHITE SOLID

② TYPE A 8" WHITE SOLID

3 TYPE A 6"YELLOW SOLID

4 TYPE A 8" YELLOW SOLID

ONE-WAY TEMPORARY PAVEMENT MARKERS SHALL BE INSTALLED ON 20'CENTERS ON LANE SHIFT TAPERS 6 GROUP 2 CHANNELIZING DEVICE

• GROUP 2 CHANNELIZING DEVICE


── IMPACT ATTENUATOR, TYPE 1, TL-3


AREA UNDER CONSTRUCTION (THIS PHASE)

PROJECT

0081-095-829

SHEET NO.






ROJECT MANAGER *James Jones, L.S. (276) 696-3257 (Bristol)*

SURVEYED BY, DATE _*Woolpert Inc., (757) 549-3549 (Nov.24,2019)*______ DESIGN BY Tamara Pritchard, P.E. (276) 696-3249 (Bristol) SUBSURFACE UTILITY BY, DATE Woolpert Inc., (757) 549-3549 (Nov. 24, 2019)

MAINTENANCE OF TRAFFIC = SEQUENCE OF CONSTRUCTION PHASE 1



VDOT Location & Design

Bristol, Virginia

ROADWAY ENGINEER


Bristol, Virginia


TRAFFIC ENGINEER

NECESSARY BY THE DEPARTMENT

PH PLANS

THESE PLANS ARE UNFINISHED AND UNAPPROVED AND ARE NOT TO BE USED FOR ANY TYPE OF CONSTRUCTION OR THE ACQUISITION OF RIGHT OF WAY.





(5) TRAFFIC BARRIER SERVICE CONCRETE, ST'D. MB-IIA

TYPE A 6" WHITE SOLID

② TYPE A 8" WHITE SOLID

3 TYPE A 6" YELLOW SOLID

4 TYPE A 8"YELLOW SOLID

ONE-WAY TEMPORARY PAVEMENT MARKERS SHALL BE INSTALLED ON 20' CENTERS ON LANE SHIFT TAPERS

- 6 GROUP 2 CHANNELIZING DEVICE TEMPORARY PAVEMENT MARKING
 - CONSTRUCTION SIGN
 - GROUP 2 CHANNELIZING DEVICE
 - ← TRAFFIC FLOW ARROW
 - ── IMPACT ATTENUATOR, TYPE 1, TL-3

MAINTENANCE OF TRAFFIC LEGEND

AREA PREVIOUSLY CONSTRUCTED

AREA UNDER CONSTRUCTION (THIS PHASE)

- * TYPE B WARNING LIGHT
- ESSE SHADOW VEHICLE WITH TMA


	SCALE		PROJECT	SHEET NO.
0	50'	100'	0081-095-829	IJ(II)


ROJECT MANAGER *James Jones, L.S. (276) 696-3257 (Bristol)*

SURVEYED BY, DATE <u>Woolpert Inc., (757) 549-3549 (Nov.24,2019)</u>

DESIGN BY Tamara Pritchard, P.E. (276) 696-3249 (Bristol)

SUBSURFACE UTILITY BY, DATE Woolpert Inc., (757) 549-3549 (Nov. 24, 2019)






VDOT Traffic

Bristol, Virginia

TRAFFIC ENGINEER



VDOT Location & Design

Bristol, Virginia

ROADWAY ENGINEER

TEMPORARY PAVEMENT MARKING

TYPE A 6" WHITE SOLID

② TYPE A 8" WHITE SOLID

3 TYPE A 6"YELLOW SOLID

4 TYPE A 8" YELLOW SOLID


ONE-WAY TEMPORARY PAVEMENT MARKERS SHALL BE INSTALLED ON 20' CENTERS ON LANE SHIFT TAPERS


NECESSARY BY THE DEPARTMENT


PH PLANS

C-50i

THESE PLANS ARE UNFINISHED AND UNAPPROVED AND ARE NOT TO BE USED FOR ANY TYPE OF CONSTRUCTION OR THE ACQUISITION OF RIGHT OF WAY.







<u>MAINTENANCE OF TRAFFIC LEGEND</u>

AREA UNDER CONSTRUCTION (THIS PHASE)

AREA PREVIOUSLY CONSTRUCTED

(5) TRAFFIC BARRIER SERVICE CONCRETE, ST'D. MB-IIA

6 GROUP 2 CHANNELIZING DEVICE

• CONSTRUCTION SIGN

• GROUP 2 CHANNELIZING DEVICE


← TRAFFIC FLOW ARROW

── IMPACT ATTENUATOR, TYPE 1, TL-3

* TYPE B WARNING LIGHT

SHADOW VEHICLE WITH TMA

SHEET NO. 0081-095-829



PROJECT MANAGER <u>James Jones, L.S. (276) 696-3257 (Bristol)</u> Surveyed by, date <u>Woolpert Inc., (757) 549-3549 (Nov. 24, 2019)</u>

DESIGN BY <u>Tamara Pritchard, P.E. (276) 696-3249 (Bristol)</u>
SUBSURFACE UTILITY BY, DATE <u>Woolpert Inc.</u>, (757) 549-3549 (Nov. 24, 2019)

DESIGN FEATURES RELATING TO CONSTRUCTION
OR TO REGULATION AND CONTROL OF TRAFFIC
MAY BE SUBJECT TO CHANGE AS DEEMED
NECESSARY BY THE DEPARTMENT

VDOT Traffic

Bristol, Virginia TRAFFIC ENGINEER VDOT Location & Design

Bristol, Virginia ROADWAY ENGINEER

TEMPORARY PAVEMENT MARKING

TYPE A 6" WHITE SOLID

② TYPE A 8" WHITE SOLID

3 TYPE A 6"YELLOW SOLID

4 TYPE A 8" YELLOW SOLID

ONE-WAY TEMPORARY PAVEMENT MARKERS SHALL BE INSTALLED ON 20'CENTERS ON LANE SHIFT TAPERS PH PLANS

THESE PLANS ARE UNFINISHED AND UNAPPROVED AND ARE NOT TO BE USED FOR ANY TYPE OF CONSTRUCTION OR THE ACQUISITION OF RIGHT OF WAY.

6 GROUP 2 CHANNELIZING DEVICE

• GROUP 2 CHANNELIZING DEVICE

── IMPACT ATTENUATOR, TYPE 1, TL-3

PROJECT

0081-095-829


SHEET NO.

• CONSTRUCTION SIGN

← TRAFFIC FLOW ARROW

* TYPE B WARNING LIGHT

ESSE SHADOW VEHICLE WITH TMA



TEMP.PAVEMEN


MARKING

PREVIOUSLY STABILIZED -SHOULDER

MAINTENANCE OF TRAFFIC =

SEQUENCE OF CONSTRUCTION

PHASE 2



ROJECT MANAGER *James Jones, L.S. (276) 696-3257 (Bristol)* SURVEYED BY, DATE <u>Woolpert Inc., (757) 549-3549 (Nov.24,2019)</u>

DESIGN BY Tamara Pritchard, P.E. (276) 696-3249 (Bristol) SUBSURFACE UTILITY BY, DATE Woolpert Inc., (757) 549-3549 (Nov. 24, 2019)

VA.

0081-095-829, RW-201

VDOT Location & Design VDOT Traffic Bristol, Virginia Bristol, Virginia

ROADWAY ENGINEER

TEMPORARY PAVEMENT MARKING

() TYPE A 6" WHITE SOLID

② TYPE A 8" WHITE SOLID

3 TYPE A 6" YELLOW SOLID


♠ TYPE A 8"YELLOW SOLID

ONE-WAY TEMPORARY PAVEMENT MARKERS SHALL BE INSTALLED ON 20'CENTERS ON LANE SHIFT TAPERS

TRAFFIC ENGINEER

PH PLANS


THESE PLANS ARE UNFINISHED AND UNAPPROVED AND ARE NOT TO BE USED FOR ANY TYPE OF CONSTRUCTION OR THE ACQUISITION OF RIGHT OF WAY.



MAINTENANCE OF TRAFFIC =

SEQUENCE OF CONSTRUCTION

PHASE 2



MAINTENANCE OF TRAFFIC LEGEND

AREA UNDER CONSTRUCTION (THIS PHASE)

AREA PREVIOUSLY CONSTRUCTED

(5) TRAFFIC BARRIER SERVICE CONCRETE, ST'D. MB-IIA

6 GROUP 2 CHANNELIZING DEVICE

• CONSTRUCTION SIGN

• GROUP 2 CHANNELIZING DEVICE

← TRAFFIC FLOW ARROW

── IMPACT ATTENUATOR, TYPE 1, TL-3

* TYPE B WARNING LIGHT


SHADOW VEHICLE WITH TMA


SHEET NO. 0081-095-829

ROJECT MANAGER *James Jones, L.S. (276) 696-3257 (Bristol)*

SURVEYED BY, DATE <u>Woolpert Inc., (757) 549-3549 (Nov.24,2019)</u> DESIGN BY Tamara Pritchard, P.E. (276) 696-3249 (Bristol) SUBSURFACE UTILITY BY, DATE Woolpert Inc., (757) 549-3549 (Nov. 24, 2019)

MAINTENANCE OF TRAFFIC = SEQUENCE OF CONSTRUCTION PHASE 2





SIGN

R/S

Plotted By: elilley
LIMITED ACCESS HIGHWAY

By Resolution of Highway Commission dated October 4, 1956

REVISED STATE ROUTE PROJECT 0081-095-829, RW-201 VA. 81 C-50i

> DESIGN FEATURES RELATING TO CONSTRUCTION OR TO REGULATION AND CONTROL OF TRAFFIC MAY BE SUBJECT TO CHANGE AS DEEMED NECESSARY BY THE DEPARTMENT

I-81 CONSTRUCTABILITY PLAN REVIEW TEAM MEMBERS

Marty Halloway - Construction Brian Plummer - Construction Clay Stowers - Materials Bill Lester - Materials Jeremy Mullins - Traffic George Young - Environmental Dennis Sanders - Environmental Bishard Buskingham - Hydraulics Richard Buckingham - Hydraulics Josh Lewis - Hydraulics David Duncan - Right of Way Josh Sproles - Utilities

STORMWATER MANAGEMENT

- S-1 CLEARING AND GRUBBING OF SWM BASIN SITE The area where the dam is to be constructed and the area upstream of the dam, to an elevation equal to the crest of the dam (maximum ponded water elevation), shall be cleared and grubbed in accordance with Section 301 of the applicable VDOT Road and Bridge Specifications.
- S-2 SWM BASIN DAM CONSTRUCTION The dam for detention basins (no permanent pool) shall conform to the details contained in the plans and shall be constructed in accordance with Section 303 of the applicable VDOT Road and Bridge Specifications. The native material on which the dam will set shall meet the specifications for AASHTO Type A-4 or finer material. Where the native material does not meet this requirement, the area beneath the dam is to be excavated a minimum of 4' and backfilled with a material meeting the AASHTO Type A-4 or finer classification unless otherwise specified in the plans. The material used for the embankment of the dam shall be AASHTO Type A-4 or finer or otherwise specified in the plans. Dams with foundation and embankment material not meeting the above requirements or dams greater than 15' in height, or dams for retention basins (permanent pool) shall incorporate a membrane-lined trench, a homogenous embankment with seepage controls, a zoned embankment or other such approved designs as specified in the plans.
- S-3 SWM BASIN OUTLET PIPE The pipe culvert under or through the dam for detention basins (no permanent pool) shall be reinforced concrete pipe with rubber gaskets in accordance with Section 232 and 212 of the applicable VDOT Road and Bridge Specifications. A concrete cradle shall extend the full length of the pipe culvert in accordance with the Standard Drawings. The connection between the pipe culvert and the SWM-1 Drainage Structure (or other control structure) shall be made watertight as approved by the Engineer and the cost shall be included in the price bid for pipe.
- S-4 The SWM-1 Drainage Structure (or other control structure) shall have 4" high numbers and 1" wide stripes painted at 1 intervals as shown on the Standard Drawings or detail sheets. The numbers and stripes are to be installed at the time of the initial installation of the SWM-1 Drainage Structure (or other control structure). Paint and application shall be in accordance with Section 231 and 411 of the applicable VDOT Road and Bridge Specifications and the cost is to be included in the price bid for the applicable structure.
- S-4 The SWM-1 Drainage Structure (or other control structure) shall have 4" high numbers and 1" wide stripes painted at 1 intervals as shown on the Standard Drawings or detail sheets. The numbers and stripes are to be installed at the time of the initial installation of the SWM-1 Drainage Structure (or other control structure). Paint and application shall be in accordance with Section 231 and 411 of the applicable VDOT Road and Bridge Specifications and the cost is to be included in the price bid for

PH PLANS

THESE PLANS ARE UNFINISHED AND UNAPPROVED AND ARE NOT TO BE USED FOR ANY TYPE OF CONSTRUCTION OR THE ACQUISITION OF RIGHT OF WAY.

> **PROJECT** SHEET NO. 0081-095-829

GENERAL NOTES

GRADING

PROJECT MANAGER *James Jones, L.S. (276) 696-3257 (Bristol)*

SURVEYED BY, DATE *Woolpert Inc., (757) 549-3549 (Nov.24,2019)*

DESIGN BY Tamara Pritchard, P.E. (276) 696-3249 (Bristol) SUBSURFACE UTILITY BY, DATE Woolpert Inc., (757) 549-3549 (Nov. 24, 2019)

- G-1 The grade line denotes top of finished pavement unless shown otherwise on typical sections or plans.
- G-3 Earthwork quantities on this project are based on anticipated settlement and may require adjusting during construction. Payment will be made only for quantities actually moved.
- G-4 The cost of removal of all existing concrete items located in the area to be graded, including, but not limited to the following, shall be included in the price bid for regular excavation: -
- G-6 The borrow material for this project shall be a minimum CBR 5 or as approved by the Materials Engineer.

DRAINAGE

- D-1 The horizontal location of all drainage structures shown on these plans is approximate only, with the exception of structures showing specific stations, special design bridges and storm sewer systems.
- D-2 The horizontal location and invert elevations shown for proposed culverts and storm sewer outfall pipes are based on existing survey data and required design criteria. If during construction, it is found that the horizontal location or invert elevations shown on the plans differ significantly from the horizontal location or elevations of the stream or swale in which the culvert or storm sewer outfall pipe is to be placed, the Engineer shall confer with, and get approval from, the applicable District Drainage Engineer before installing the culvert or storm sewer outfall pipe.
- D-3 The "H" dimensions shown on plans for drop inlets and junction boxes and the "L.F." dimensions shown for manholes are for estimating purposes and are based on the proposed invert elevations shown for the structure and the anticipated top (rim) elevation based on existing or proposed finished grade. The actual "H" or "L.F." dimensions are to be determined by the contractor from field conditions.
- D-6 Pipes shall conform to any of the allowable types shown on sheet number ____ , within the applicable height of cover limitations. For strength, sheet thickness, or class designation; available sizes; height of cover limitations; and other restrictions for a particular pipe type or height of cover, see the VDOT <u>Road and Bridge Standard</u> PC-1. Structural plate pipe may be substituted for corrugated pipe of the same size, provided the substitution complies with the applicable sections of the VDOT Road and Bridge Standards PC-1.
- D-10 The proposed riprap may be omitted by the Engineer if the slope designated for placement of riprap is found to be comprised of solid rock or closely consolidated boulders with soundness, size and weight equal to, or exceeding, the specifications for the proposed riprap.
- D-13 Existing drainage facilities being utilized as a part of the drainage system, and designated on the plans "To Be Cleaned Out" shall be cleaned as directed by the Engineer. The cost incidental to this shall be included in the contract price for other items.
- D-14 Proposed drop inlets with a height (H) less than the standard minimum shown in the VDOT <u>Road and Bridge Standards</u> shall be considered and paid for as Standard Drop Inlets for the type specified. Pipes with less than standard minimum finished height of cover shall be noted as such in the drainage description for the pipe. Specific pipe bedding and cover requirements are provided in the applicable PB-1 and PC-1 standard drawings of the VDOT Road and Bridge Standards.
- D-17 St'd. SL-1 Safety Slab locations are based on the assumed use of precast structures. If cast-in-place structures are utilized, and the interior chamber dimensions (length and width, or diameter) are less than 4 feet, the safety slabs shall not be installed.

PAVEMENT

P-2 The pavement materials on this project will be paid for on a tonnage basis. The weight will vary in accordance with the specific gravity of the aggregates and the asphaltic content of the mix actually used to secure the design depth. The weight of the asphalt concrete is based on 95% of the theoretical maximum density.

INCIDENTALS

- 1-7 Where Standard slope roundoffs would damage trees, bushes or other desirable vegetation, they shall be omitted when so ordered by the Engineer.
- I-8A Clearing and grubbing shall be confined to those areas needed for construction. No trees or shrubs in ungraded areas shall be cut without the permission of the Engineer.

- 1-14 Salvaged guardrail materials not used in the new construction shall become the property of the Contractor and shall be disposed of at a licensed landfill, recycled or be retained by the Contractor.
- I-17 For method of constructing Straight-Line Taper Lanes in curb and/or curb and gutter sections, see typical details on Sheet 2A.
- 1-18 All pavement markings and traffic flow arrows shown on the roadway construction plans are schematic only. The actual location and application of pavement markings shall be in accordance with Section 704 of the applicable VDOT Road and Bridge Specifications, MUTCD, sequence of construction/ traffic control plans, pavement marking plan sheets ___ thru ___ and as directed by the Engineer.
- 1-19 The following outside sources, under contract with VDOT, have provided information on this project.

Utility Design -

- If questions or problems arise during construction, please contact the Area Construction Engineer. DO NOT CONTACT THE OUTSIDE SOURCES.
- 1-20 The Official Electronic PDF Version of the plans will override the paper copies or prints of specific layers.

Portions of this plan assembly have been CADD generated. To assist in the preparation of the bid and construction of the project, Microstation format (.dgn) files will be made available to the prime contractor during bids and after award of the contract.

1-21 All electronic plan assemblies will include the construction plans in two formats: PDF files and MicroStation format (.dgn) files. Only the PDF files will be considered as part of the official plan assembly.

The MicroStation format (.dgn) files are furnished only as information for the contractor. These plans are developed in layers (levels) to aid in readability. (See the VDOT CADD Manual for CADD Level Structure). However, the construction items may or may not be in the proper layering scheme as described in the VDOT CADD Manual. The Microstation files will only match the scanned files if all required levels are turned on. A Microstation Software license is required to be able to read these files.

NOTE: Existing shoulder material comprised of stone cannot be used on the exterior portion of proposed slopes.

EROSION AND SEDIMENT CONTROL (ESC)


- E-1 If the removal of Brush Silt Barrier is specified by the plans or required by the Engineer, the cost of removal and disposal of brush shall be in accordance with Section 109 of the applicable VDOT Road and Bridge Specifications.
- E-2 Rock for Check Dams, Inlet Protection, Erosion Control Stone and Riprap shall be in accordance with Section 203 and Section 414 of the applicable VDOT Road and Bridge Specifications.
- E-3 The following symbols are used to depict Erosion Control items in the plan assembly:



E-4 Permanent vegetation shall be established on all denuded areas not otherwise stabilized with non-erodible materials. See the Roadside Development sheet for details on permanent vegetation establishment.

LIMITED ACCESS HIGHWAY

By Resolution of Highway Commission dated October 4, 1956



()

The information contained in the SWPPP General Information sheets is intended to comply with the requirements of the VPDES General Permit For Discharges Of

The SWPPP General Information sheets are to be completed and included in the construction plan set (or other such documents) for land disturbance activities that disturb an area equal to or greater than 10,000 square feet outside the Chesapeake Bay Preservation Area, or equal to or greater than 2,500 square feet in the area defined as Tidewater, Virginia in the Virginia Chesapeake Bay Preservation Act.

Stormwater From Construction Activities (the VPDES Construction Permit) issued

July 1, 2019 and VDOT's approved Annual ESC and SWM Standards and Specifications.

The VDOT RLD (as defined in the latest IIM 242) will ensure that the information shown on the SWPPP GeneralInformation sheets is updated/revised as necessary in order to reflect changes that may occur during the construction phase of the land disturbing (construction) activity. The updated/revised sheets shall be maintained with the designated record set of plans (or other such documents) for the land disturbance (construction) activity.

Icertify under penalty of law that I have read and understand this document and that this document and all attachments were prepared in accordance with a system designed to assure that qualified personnel properly gathered and evaluated the information submitted. Based on my inquiry of the person or persons who manage the system, or those persons directly responsible for gathering the information, the information submitted is, to the best of my knowledge and belief, true, accurate, and complete. I am aware that there are significant penalties for submitting false information, including the possibility of fine and imprisonment for knowing violations.

I further certify that this document and all other documents related to the SWPPP, as identified on the SWPPP General Information Sheets, are maintained at the activity site, or at a location convenient to the activity site where no on-site facilities are available, and such documents will be made available for review upon request in accordance with the provisions of the General VPDES Permit for Discharges of Stormwater from Construction Activities (VAR10) when applicable. Where the SWPPP documents are not stored on-site, a copy of such documents shall be in the possession of those with day to day operational control over the implementation of the SWPPP whenever they are on site.

* or ** Delegated Authority Signature"

Signature: _____Printed Name: Brian Plummer, P.E. Date:_____

(1) See Section 1, Item 11 relating to delegation of authority, and form LD-445H (Delegation of Authority).

ACRONYMS

CBPA - Chesapeake Bay Preservation Act BMP - Best Management Practice

DEQ - Department of Environmental Quality EPA - U.S. Environmental Protection Agency

ESC - Erosion and Sediment Control

IIM - Instructional and Informational Memorandum R&B - Road and Bridge RLD - Responsible Land Disturber

SWPPP - Stormwater Pollution Prevention Plan

TMDL - Total Maximum Daily Load VDOT - Virginia Department of Transportation

VPDES - Virginia Pollutant Discharge Elimination System VSMP - Virginia Stormwater Management Program

VESCP - Virginia Erosion and Sediment Control Program

WLA - Waste Load Allocation SWM - Stormwater Management

SECTION I GENERAL INFORMATION

- 1. Activity Description Grading, Paving, and Drainage for an additional Truck Climbing Lane.
- 2. This land disturbance (construction) activity site is located in Washington County and approximately 9.97 acres will be disturbed by excavation, grading or other construction activities.
- 3. Coverage
- A. This proposed activity disturbs one acre or greater and requires coverage under the VPDES General Permit for Discharges Of Stormwater from Construction Activities (the VPDES Construction Permit) as issued by the DEQ. A copy of the VPDES Construction Permit (VAR10), the registration information (LD-445 & LD-445C forms) and the permit coverage letter received from DEQ shall be maintained with other SWPPP documents for this land disturbing activity.

XX 4. The location of on-site support facilities that will be covered under the VPDES Construction Permit coverage for this land disturbance (construction) activity shall be provided by the contractor and identified on the record set of plans or in other appropriate contract documents. Support facilities shall include, but not be limited to. borrow and disposal areas, construction and waste material storage areas, equipment and vehicle washing, maintenance, storage and fueling areas, storage areas for fertilizers, fuels or chemicals, concrete wash out areas, sanitary waste facilities and any other areas that may generate a stormwater or non-stormwater discharge directly related to the construction site.

STORMWATER POLLUTION PREVENTION PLAN (SWPPP) GENERAL INFORMATION SHEET

- XX 5. Written Evidence of permit coverage shall be provided by the contractor for all support activities located outside of VDOT right of way or easement in the form of the Construction General Permit coverage letter: (List VPDES Permit * or Letter from VSMP Authority stating coverage not needed)
 - 6. List the surface waters that have been identified as impaired in the DEQ 2012 305(b)/303(d) Water Quality Assessment Integrated Report for sediment, total suspended solids, turbidity, Nitrogen or Phosphorus. These pollutants are considered benthic impairments: (List the impaired surface waters, when applicable)
 - 7. Identify the TMDL's where stormwater from construction activities discharges into a watershed with a TMDL waste load allocation established and approved by the State Water Control Board prior to July 1, 2016 for sediment, total suspended solids, turbidity, nitrogen or phosphorus:(List the TMDL and pollutant(s)of concern. when applicable)
 - 8. This land disturbance activity discharges stormwater to the following surface waters that have been identified as exceptional in Section 9VAC25-260-30 A 3 c of the Virginia Administrative Code: (List name of surface waters) or not applicable (N/A).
 - 9. Locations of surface waters and locations where concentrated stormwater is discharged from this land disturbance (construction) activity are identified in the construction plan set (or other such documents) for this land disturbance (construction) activity. (List name of surface waters and locations here if not shown in construction plan or other such documents).
 - 10. The ESC and SWM plans (where applicable) for this land disturbance (construction) activity have been developed in accordance with VDOT's Approved Annual Erosion and Sediment Control and Stormwater Management Standards and Specifications as approved by the DEQ.
 - 11. List the RLD and other responsible parties for the land disturbance activity: (required for erosion and sediment control). The following individual(s) have "delegated authority" to sign all reports required by the construction permit including the SWPPP General Information Sheets and Inspection Reports (C-107). Reference form LD-445H for delegation of authority (form 445H for the project is hereby incorporated by reference into this SWPPP). These individual(s) has/have overall responsibility or the environmental matters for the project: (required only for permitted projects):

Name	Position	Responsibility

Brian Plummer, P.E.	RLD	Certify the SWPPP (with date & sig.)
	Certified Inspector	Sign (C-107) Inspection Form Part 1
	Certified Inspector	Sign (C-107) Inspection Form Part 2

X 12. The name of the VDOT individual(s) responsible for the oversight inspection in accordance with IIM-LD-256 on these land disturbance construction activities as identified on these SWPPP General Information Sheets. The names will be updated and maintained with the other SWPPP documents for this land disturbance activity.

VDOT Individuals	Position	Responsibility
Derrick Dotson	NPDES	NPDES coordinator responsible for the oversight inspection in accordance with IIM-LD-256
Richard Buckingham, P.E.	Dist. Hyd. Engineer	District Hydraulic Engineer or designee(s) responsible for the review & the coordination approval of ESC SWM plan modification(s).

STATE ROUTE PROJECT 0081-095-829,PE-101, VA. | 8/ RW-201.C-501

DESIGN FEATURES RELATING TO CONSTRUCTION OR TO REGULATION AND CONTROL OF TRAFFIC MAY BE SUBJECT TO CHANGE AS DEEMED NECESSARY BY THE DEPARTMENT

- X 13. The ESC and P2 inspections for this land disturbing (construction) activity shall follow (Select Schedule 1 or 2, if schedule #2 is used, void note #14) as defined in 2016 R&B Specifications except for Section 107.16(e) 4.an Inspection Requirements Rain gauge notes apply only to Inspection Schedule 1.
- XX 14. The location of the on-site rain gage that will be used to determine the occurrence of a measurable storm event for the purposes of ESC and Pollution Prevention inspections will be provided by the contractor and identified on the record set of plans or in other appropriate SWPPP documents for this land disturbance activity: (List location of rain gage).

The rain gage shall be observed daily at "_____ ____' to determine the occurrence of a measurable storm event (i.e., 0.25 inches of rainfall or greater in a 24 hour period). A log book shall be maintained to record observation information which shall include (1) the date, (2) the time, (3) whether or not rainfall is occurring at the time of the observation, (4) the amount of accumulated rainfall in the gage, if any, and (5) whether or not an inspection is required based on the amount of accumulated rainfall in the gage. If there is no rainfall occurring at the time of the observation, the observation information shall be noted in the log book and the rain gage emptied and replaced. An inspection is required if there is 0.25 inches or more accumulation noted in the rain gage. If there is rainfall occurring at the time of the observation, the observation information is to be noted in the log book. The rain gage is not to be emptied but left to accumulate additional rainfall until the conclusion of the rainfall event. At the conclusion of the rainfall event, an observation of the rain gage shall be made and the observation information shall be noted in the log book and the rain gage emptied and replaced. An inspection is required if there is 0.25 inches or more accumulation noted in the rain gage.

15. The following VDOT documents are applicable to a) permitted projects b) non-permitted projects in Chesapeake Bay Preservation Areas (CBPA) with 2,500 S.F. to 1.0 acre of land disturbance c) non-permitted projects requiring a SWPPP and d) Non-permitted, Non-CBPA with BMP projects that have a water quantity BMP:

> VDOT LD-445: Permitted projects, CBPA projects and Non-permitted, Non-CBPA with BMP projects that have a water quantity BMP and ESC projects > 10,000 s.f. but <1 acre.

VDOT LD-445A: Permitted projects only. VDOT LD-445C: Projects that require a permit, ESC Plan, or SWPPP. VDOT LD-445D: Permitted projects, CBPA projects and Non-permitted,

Non-CBPA with BMP projects that have a water quantity BMP. VDOT LD-445F: Emergency work projects (when applicable).

Water Quality Requirement (when applicable)

VDOT LD-445H: Permitted projects only. VDOT C-107 Part Land Part II. All projects that require a permit or SWPPP. VDOT LD-445I: AS&S Approval Form (when applicable)

16. If there is an excessive loading of sediment from the project (i.e. more than to be expected from the project with an implemented ESC plan) that is discovered within a local watershed with a sediment TMDL that allocates a WLA to VDOT's MS4. (see note #7) the contractor shall investigate the area of concern at the site within 24 hours of discovery and ensure all erosion and sediment control best management practices are being implemented in accordance with the permits approved standards and specifications required by Part I.B of the current Construction General Permit. If corrective action is necessary, the contractor shall initiate corrective actions no later than 5 business days after the initial investigation.

17. If excessive loading of sediment from a land disturbing activity that is not the responsibility of the contractor is discovered discharging into a MS-4, the contractor shall notify the municipality with jurisdiction over erosion and sediment control activities.

> X Denotes information that is to be provided/completed by the RLD.

** Denotes information that is to be provided/completed by the contractor.

Revised 5/1/19

0081-095-829

SHEET NO. 2B(I)

PROJECT MANAGER <u>James Jones, L.S.(276) 696-3257 (Bristol)</u>

SURVEYED BY, DATE *Woolpert Inc., (757) 549-3549 (Nov. 24, 2019)* DESIGN BY Rebekah Stroupe, P.E. (276) 696-3369 (Bristol) SUBSURFACE UTILITY BY, DATE Woolpert Inc., (757) 549-3549 (Nov. 24, 2019)

LIMITED ACCESS HIGHWAY By Resolution of Highway Commission dated October 4, 1956

REVISED STATE ROUTE PROJECT 0081-095-829,PE-101, 2B(2) VA. 8/ RW-201.C-501

DESIGN FEATURES RELATING TO CONSTRUCTION MAY BE SUBJECT TO CHANGE AS DEEMED

SWPPP - Stormwater Pollution Prevention Plan

VDOT - Virginia Department of Transportation

VPDES - Virginia Pollutant Discharge Elimination System

VESCP - Virginia Erosion and Sediment Control Program

VSMP - Virginia Stormwater Management Program

TMDL - Total Maximum Daily Load

WLA - Waste Load Allocation

SWM - Stormwater Management

NECESSARY BY THE DEPARTMENT

OR TO REGULATION AND CONTROL OF TRAFFIC

- 5. A description of all post-construction stormwater management measures that will be installed during the construction process to control pollutants in stormwater discharges after construction operations have been completed is included in the construction plan set (or other such documents) for this land disturbance (construction) activity.
- 6. All engineering calculations supporting the design of the post-construction stormwater management measures for this land disturbance (construction) activity, including an explanation of the technical basis used to select the practices, are contained in the project drainage file located in the (insert appropriate location, i.e., VDOT Central Office Hydraulics Section or the VDOT (specify) District Hydraulics Section or the VDOT (specify) Residency Office) and will be made available for review upon request during normal working business hours.

SECTION II EROSION AND SEDIMENT CONTROL

- $\mathbb{X}\mathbb{X}$ 1. The intended sequence and timing of activities that disturb soils at the site (e.g., grubbing, excavation, grading, utilities and infrastructure installation, etc.) shall be provided by the contractor in accordance with the current edition of Section 108.03 of the VDOT R&B Specifications and shall be included with the other SWPPP documents for this land disturbance (construction) activity.
 - 2. Directions of stormwater flow and approximate slopes anticipated after major grading activities are identified in the construction plan set (or other such documents) for this land disturbance (construction) activity.
 - 3. Areas of soil disturbance and areas of the site which will not be disturbed are identified in the construction plan set (or other such documents) for this land disturbance (construction) activity.
 - 4. Locations of major structural and nonstructural ESC measures intended to filter, settle or similarly remove sediment are identified in the construction plan set (or other such documents) for this land disturbance (construction) activity.
 - 5. Locations where stabilization practices are expected to occur are identified in the construction plan set (or other such documents) for this land disturbance (construction) activity.
 - 6. A description of interim and permanent stabilization practices for the site are identified in the applicable sections of the documents identified in the Note 1 of Section IV.
- XX 7. A record of the dates when major grading activities occur, when construction activities temporarily or permanently cease on a portion of the site, and when stabilization measures are initiated will be provided by the contractor and maintained with the record set of plans or other SWPPP documents for this land disturbance (construction) activity: (List how this will be tracked and the location)
 - 8. A description and schedule of procedures to maintain vegetation, erosion and sediment control measures and other protective measures in good and effective operating conditions are identified in the current edition of Sections 107.16 and 303.03 of the VDOT R&B Specifications.
 - 9. Nutrients shall be applied in accordance with the current edition of Sections 603 and 604 of the VDOT Road and Bridge Specifications. Nutrients shall not be applied during rainfall events. Top soil shall be applied in accordance with the current edition of section 602 of the latest Road and Bridge Specifications.
 - 10. All engineering calculations supporting the design of erosion and sediment control measures proposed for this land disturbance (construction) activity are contained in the project drainage file located in the Bristol District Hydraulics Section and will be made available for review upon request during normal business hours.
 - 11. The temporary erosion and siltation controlitems shown on the ESC Plan for this land disturbing (construction) activity are intended to provide a general plan for controlling erosion and sediment within the project limits. The ESC Plan is based on field conditions at the time of plan development and an assumed sequence of construction for the project. The contractor, in conjunction with the VDOT Project Engineer and/or ESC Inspector, shall adjust the location, quantity and type of erosion and sediment controlitems required based on the actual field conditions encountered at the time of construction and the actual scheduling and sequencing of the construction activities. Significant changes to the proposed ESC Plan (e.g., those that require an engineering analysis, elimination of a perimeter control, change to ESC concept that would affect the quantity or direction of flow of water) shall be submitted to the applicable District Hydraulics Engineer for review and approval. Any changes to the proposed ESC Plan must be noted on the designated record set of plans which shall be retained on the project site and made available upon request during normal business hours.
 - 12. The areas beyond the project's construction limits are to be protected from siltation. Perimeter controls such as silt fence, diversion dikes, turbidity curtains, etc. shall be installed prior to any grubbing operations or other earth moving activities.
 - 13. Temporary earthen structures such as dikes and berms are to be stabilized immediately upon installation. Stabilization may include temporary or permanent seeding, riprap, aggregate, sod, mulching, and/or soil stabilization blankets and matting in conjunction with seeding.
 - 14. All channel relocations are to be constructed during the earliest stage of construction and shall be constructed in accordance with all applicable permit requirements and shall be constructed in the dry wherever possible. Stabilization or vegetation shall be established before flow is redirected through the constructed area as directed by the Engineer.
 - 15. The contractor shall plan and implement his land disturbance operations in order to:
 - a. Control the volume and velocity of stormwater runoff within the site to minimize erosion.
 - b. Control the peak flow rates, volume and velocity of stormwater discharges to minimize erosion at outlets and in downstream channels.
 - c. Minimize the amount of soil exposed.
 - d. Minimize the disturbance of steep slopes.
 - e. Minimize sediment discharge from the site.
 - f. Provide and maintain natural buffers around surface waters, direct stormwater runoff to vegetated areas and maximize stormwater infiltration, unless infeasible.
 - g. Minimize soil compaction (except in those areas where compaction is required by the contract documents) and preserve topsoil where feasible.

- ★米 16. The name of the individual(s) or contractor(s) responsible for the installation and maintenance of the erosion and sediment control measures shall be supplied by the contractor and maintained with the other SWPPP documents for this land disturbance (construction) activity.
 - 17. Soil stockpiles temporarily placed within the project area or on VDOT right of way or easement shall be identified, stabilized, and protected with sediment trapping measures.
 - 18. A construction entrance or other approved measure shall be installed at all locations where construction vehicular traffic access routes intersect a paved or a public road in order to minimize the transport of sediment by vehicular tracking onto the paved surface. Where sediment is transported onto a paved or a public road surface, the road shallbe cleaned thoroughly at the end of each work day by shoveling or sweeping. Removed sediment shall be disposed of in accordance with Section 106.04 of the R&B Specifications.
 - 19. Any variance, exception or deviation approved by DEQ must be listed below and supporting documentation (exception/variance/deviation request and DEQ approval) must be maintained with the SWPPP.
 - The following exceptions to the Water Quantity criteria of the VSMP Regulation have been approved by the DEQ for this land disturbance (construction) activity: (list all approved exceptions and include a brief description of the exception, the date approved and the approving DEQ Office)

Type(1)	Regulation Modified(2)	Approval Date(3)	Description of Variance

- (1) Type of modification (Variance from ESC regulations, or Deviation
- from published guidance)
- (2) Section of Regulation or Guidance Document Modified (e.g. ESC Min. Std. 15)
- (3) Date that variance/exception/deviation was approved by DEQ.

SECTION III POST CONSTRUCTION STORMWATER MANAGEMENT

Choose the appropriate note 1A or 1B that is applicable to the proposed post construction SWM Plan for this land disturbance (construction) activity. (Delete, strikethrough or mark as NA those notes not applicable.)

- 1. (Include one of the following notes as appropriate)
- ** A. This land disturbance activity is grandfathered under Section 9VAC25-870-48 of the VSMP Regulations and utilizes the Part IIC technical -criteria (i.e., Performance or Technology Based, MS 19, etc.) in Section 9VAC25-870-93 et seg. of the VSMP Regulations.
- X B. This land disturbance activity utilizes the Part IIB technical criteria (i.e., Runoff Reduction Method, Energy Balance Equation, etc.) in Section 9VAC25-870-62 et seq. of the VSMP Regulations.
- 2. An exception for (number) pounds of phosphorus removal has been granted for this land disturbance activity by the DEQ in its letter dated (date).
- 3. Any variance, exception or deviation approved by DEQ must be listed below and supporting documentation (exception/variance/deviation request and DEQ approval) must be maintained with the SWPPP.

The following exceptions to the Water Quantity criteria of the VSMP Regulation have been approved by the DEQ for this land disturbance activity: (list all approved exceptions and include a brief description of the exception, the date approved and the approving DEQ

Type(1)	Regulation Modified(2)	Approval Date(3)	Description of Waiver

- (1) Type of modification (Variance, or Exception from SWM Regulations
- or Deviation from published guidance)
- (2) Section of Regulation or Guidance Document Modified (e.g. ESC Min. Std. 15)
- (3) Date that variance/exception/deviation was approved by DEQ.
- 4. The permanent onsite SWM facilities or offsite strategies proposed to meet the water quality/quantity requirements for this land disturbance (construction) activity are listed in Section VI.

ACRONYMS

CBPA - Chesapeake Bay Preservation Act

BMP - Best Management Practice DEQ - Department of Environmental Quality

EPA - U.S. Environmental Protection Agency

ESC - Erosion and Sediment Control IIM - Instructional and Informational Memorandum

R&B - Road and Bridge

RLD - Responsible Land Disturber

X Denotes information that is to be provided/ completed by the RLD.

** Denotes information that is to be provided/completed by the contractor.

Revised 5/1/19

SHEET NO. 0081-095-829 2B(2)

LIMITED ACCESS HIGHWAY By Resolution of Highway Commission dated October 4, 1956

STATE ROUTE PROJECT 0081-095-829,PE-101, 2B(3) VA. | 8/ RW-201, C-501

MAY BE SUBJECT TO CHANGE AS DEEMED NECESSARY BY THE DEPARTMENT

DESIGN FEATURES RELATING TO CONSTRUCTION OR TO REGULATION AND CONTROL OF TRAFFIC

STORMWATER POLLUTION PREVENTION PLAN (SWPPP) GENERAL INFORMATION SHEET

The information contained in the SWPPP General Information sheets is intended to comply with the requirements of the VPDES General Permit For Discharges Of Stormwater From Construction Activities (the VPDES Construction Permit) issued July 1, 2019 and VDOT's approved Annual ESC and SWM Standards and Specifications.

The SWPPP General Information sheets are to be completed and included in the construction plan set (or other such documents) for land disturbance (construction) activities that disturb an area equal to or greater than 10,000 square feet outside the Chesapeake Bay Preservation Area, or equal to or greater than 2,500 square feet in the area defined as Tidewater, Virginia in the Virginia Chesapeake Bay Preservation Act.

The VDOT RLD will ensure that the information shown on the SWPPP General Information sheets is updated/revised as necessary in order to reflect changes that may occur during the construction phase of the land disturbing (construction) activity. The updated/revised sheets shall be maintained with the designated record set of plans (or other such documents) for the land disturbance (construction) activity.

SECTION IV SWPPP

PROJECT MANAGER <u>James Jones, L.S.(276) 696-3257 (Bristol)</u>

SURVEYED BY, DATE *Woolpert Inc.*, (757) 549-3549 (Nov. 24, 2019) DESIGN BY Rebekah Stroupe, P.E. (276) 696-3369 (Bristol) SUBSURFACE UTILITY BY, DATE Woolpert Inc. (757) 549-3549 (Nov. 24, 2019)

> 1. All documents related to the SWPPP for this land disturbance (construction) activity shall be maintained at the activity site and shall be readily available for review upon request during normal business hours. Such documents include, but are not limited to, the construction plans (or other such documents), the ESC Plan, the Pollution Prevention Plan, the post construction SWM Plan (if applicable), the VDOT R&B Standards and Specifications, Supplemental Specifications, Special Provisions and Special Provision Copied Notes. Documents related to stormwater pollution prevention which are not a part of those documents referenced above, such as copies of the VPDES Construction Permit coverage letter (when applicable) and the VPDES General Permit For Discharges Of Stormwater From Construction Activities (when applicable) and those required to be developed by the contractor for pollution prevention associated with any on-site support facilities being included in the VPDES Construction Permit coverage for this land disturbance (construction) activity are to be maintained at the activity site with the other SWPPP documents for this land disturbance (construction) activity. Where no facilities are available at the activity site to maintain the SWPPP documents, they are to be kept by or with the designated RLD at a location convenient to the activity site where they would be made available for review upon request during normal business hours.

- 2. The SWPPP and any subsequent amendments, modifications and updates shall be implemented from commencement of land disturbance until termination of VPDES Construction Permit coverage or completion of land disturbance (construction) activities where no VPDES Construction Permit coverage is required.
- ** 3. For all on-site support facilities that will be included in the VPDES Construction Permit coverage for this land disturbance (construction) activity, the contractor shall develop a SWPPP in accordance with, but not limited to, Section 106.08, 107.02 and 107.16 of the VDOT Road and Bridge Specifications. The SWPPP for the on-site support facilities shall be maintained with and become a component of the SWPPP for this land disturbance (construction) activity. Support facilities shall include, but not be limited to, borrow and disposal areas, construction and waste material storage areas, equipment and vehicle washing, maintenance, storage and fueling areas, storage areas for fertilizers, fuels or chemicals, concrete wash out areas, sanitary waste facilities and any other areas that may generate a stormwater or non-stormwater discharge directly related to the construction site.
 - 4. For those land disturbing (construction) activities requiring coverage under the VPDES Construction Permit, the SWPPP shall be made available for review upon the request of the DEQ, the EPA, the VSMP Authority, the VESCP Authority, local government officials or the operator of a municipal separate storm sewer system (MS4) receiving discharge from the construction site.
- ¥ 5. For those land disturbing (construction) activities requiring coverage under the VPDES Construction Permit, the VDOT RLD shall post, or have posted, a copy of the General Permit coverage letter and a copy of a completed LD-445A form, noting the name and contact information for the VDOT person responsible for the land disturbing (construction) activity and its SWPPP, outside the project's construction office along with other Federal and State mandated information. Where there is no construction office (e.g., a maintenance activity), the permit coverage letter and the LD-445A form are to be maintained with the other SWPPP documents for the land disturbing (construction) activity.
- 6. The SWPPP shall be made available for review by the public upon request. Such reviews shall be at a time and publicly accessible location convenient to the VDOT and shall be scheduled during normal business hours and no less than once per month.

SECTION V - POLLUTION PREVENTION PLAN

- 1. The following non-stormwater discharges from this land disturbing (construction) activity and any on-site support facilities are prohibited:
 - a. Wastewater from concrete washouts.
 - b. Wastewater from the washout and cleanout of stucco, paint, from release oils, curing compounds and other construction materials.
 - c. Fuels, oils or other pollutants used in vehicle and equipment operation and maintenance.
 - d. Oils, toxic substances or hazardous substances from spills or other releases.
 - e. Soaps, solvents or detergents used in equipment and vehicle washing.
 - f. There shall be no discharge of floating solids or visible foam in other than trace amounts
- 2. The following non-stormwater discharges from this land disturbing (construction) activity and any on-site support facilities are allowed when discharged in compliance with the VPDES Construction Permit:
 - a. Discharges from firefighting activities.
 - b. Fire hydrant flushings.
 - c. Waters used to wash vehicles or equipment where soaps, solvents or detergents have not been used and the wash water has been filtered, settled or similarly treated prior to discharge.
 - d. Water used to control dust that has been filtered, settled or similarly treated prior to discharge.
 - e. Potable water sources including uncontaminated waterline flushings managed in a manner to avoid stream impacts.
 - f. Routine external building wash down where soaps, solvents or detergents have not been used and the wash water has been filtered, settled or similarly treated prior to discharge.
 - q. Pavement wash waters where spills or leaks of toxic or hazardous materials have not occurred (or where all spilled or leaked material has been removed prior to washing), where soaps, solvents or detergents have not been used and where the wash water has been filtered, settled or similarly treated prior to discharge.
 - Uncontaminated air conditioning or compressor condensate.
 - Uncontaminated ground water or spring water.
 - . Foundation or footing drains where flows are not contaminated with process materials such as solvents.
 - k. Uncontaminated excavation dewatering, including dewatering trenches and excavations that have been filtered, settled or similarly treated prior to discharge.
 - I. Landscape irrigation.
- ЖЖ 3. The contractor shall develop a Pollution Prevention Plan to address any of his onsite operations that have a potential to generate a pollutant that may reasonably be expected to affect the quality of stormwater discharges from this land disturbance (construction) activity. The Pollution Prevention Plan shall be developed in accordance with, but not limited to, Sections 106.08, 107.02 and 107.16 of the VDOT Road and Bridge Specifications and shall include a narrative with appropriate plan detail and shall be provided on standard 8.5 x 11 inch paper or larger and shall:
 - a. Identify the potential pollutant-generating activities and the pollutant that is expected to be exposed to stormwater.
 - b. Describe the location where the potential pollutant-generating activities will occur, or if identified on the record set of plans, reference the record set of plans.
 - c. Identify all non-stormwater discharges, as described in note two of this section, that are or will be commingled with stormwater discharges from the construction activity, including any on-site support activities.
 - d. Identify the person(s) or contractor(s) responsible for implementing and maintaining the pollution prevention practice or practices for each pollutant-generating activity.
 - e. Describe the pollution prevention practices and procedures that will be implemented to:
 - 1) Prevent and respond to leaks, spills, and other releases, including procedures for expeditiously stopping, containing, and cleaning up spills, leaks, and other releases, and procedures for reporting leaks, spills, and other releases in accordance with Section 107.16 of the VDOT Road and Bridge Specifications and the requirements within the VPDES Construction Permit.

- 2) Prevent the discharge of spilled and leaked fuels and chemicals from vehicle fueling and maintenance activities.
- 3) Prevent the discharge of soaps, solvents, detergents, and wash water from construction materials, including procedures for the clean-up of stucco, paint, form release oils, and curing compounds.
- 4) Minimize the discharge of pollutants from vehicle and equipment washing, wheel wash water, and other types of washing.
- 5) Direct concrete wash water into a leak-proof container or leak-proof settling basin. The container or basin shall be designed so that no overflows can occur due to inadequate sizing or precipitation. Hardened concrete wastes shall be removed and disposed of in a manner consistent with the handling of other construction wastes. Liquid concrete wastes shall be removed and disposed of in a manner consistent with the handling of other construction wash waters and shall not be discharged to surface waters.
- 6) Minimize the discharge of pollutants from storage, handling, and disposal of construction products, materials, and wastes including building products (such as asphalt sealants, copper flashing, roofing materials, adhesives, and concrete admixtures), pesticides, herbicides, insecticides, fertilizers, landscape materials, construction and domestic wastes (such as packaging materials), scrap construction materials, masonry products, timber, pipe and electrical cuttings, plastics, styrofoam, concrete, and other trash or building materials.
- 7) Prevent the discharge of fuels, oils, and other petroleum products, hazardous or toxic wastes, waste concrete and sanitary wastes.
- 8) Address any other discharge from any potential pollutant-generating activity not listed herein.
- 9) Minimize the exposure of waste materials to precipitation by closing or covering waste containers during precipitation events and at the end of the business day, or implementing other similarly effective practices. Minimization of exposure is not required in case where the exposure to precipitation will not result in a discharge of pollutants.
- 10) Describe and implement procedures for providing pollution prevention awareness (including but not limited to prevention practices, disposal practices and appropriate disposal locations) for all applicable wastes (including any wash water), to appropriate personnel.
- X Denotes information that is to be provided/completed by the RLD.
- XX Denotes information that is to be provided/completed by the contractor.

Revised 5/1/19

 $\langle \rangle$

hl16156_02B(4).dgn

	Plotted By: elilley	
LIMITED ACCESS	HIGHWAY By Resolution of Hi	ghway Commission 956

dated October 4, 1956									
REVISED	STATE		SHEET NO.						
	STATE	ROUTE	PROJECT	SHEET NO.					
	VA.	81	0081-095-829,PE-101, RW-201,C-501	2B(4)					

OR TO REGULATION AND CONTROL OF TRAFFIC MAY BE SUBJECT TO CHANGE AS DEEMED NECESSARY BY THE DEPARTMENT

DESIGN FEATURES RELATING TO CONSTRUCTION

STORMWATER POLLUTION PREVENTION PLAN (SWPPP) GENERAL INFORMATION SHEET

The VDOT RLD will ensure that the information shown on the SWPPP General Information sheets is updated/revised as necessary in order to reflect changes that may occur during the construction phase of the land disturbing (construction) activity. The updated/revised sheets shall be maintained with the designated record set of plans (or other such documents) for the land disturbance (construction) activity.

The SWPPP General Information sheets are to be completed and included in the construction plan set (or other such documents) for land disturbance (construction) activities that disturb an area equal to or greater than 10,000 square feet, or equal to or greater than 2,500 square feet in the area defined as Tidewater, Virginia in the Virginia Chesapeake Bay Preservation Act.

July 1, 2019 and VDOT's approved Annual ESC and SWM Standards and Specifications.

The information contained in the SWPPP General Information sheets is intended to

Stormwater From Construction Activities (the VPDES Construction Permit) issued

comply with the requirements of the VPDES General Permit For Discharges Of

SECTION VI - PERMANENT BMP INFORMATION \triangle

X Denotes information that is to be completed by the RLD. () See note referenced by number in parentheses.

INSTALLE	<u>D BMP</u>	<u>INFORMATION</u>
(VDOT	Owned	I/Operated)

PROJECT MANAGER <u>James Jones, L.S.(276) 696-3257 (Bristol)</u>

SURVEYED BY, DATE *Woolpert Inc.*, (757) 549-3549 (Nov. 24, 2019) _ _ _ _ _ DESIGN BY Rebekah Stroupe, P.E. (276) 696-3369 (Bristol)

SUBSURFACE UTILITY BY, DATE Woolpert Inc. (757) 549-3549 (Nov. 24, 2019)

Plan Sheet(s) Date BMP Made Functional	Type of BMP Installed (See Table A and C)	Geographic Location (County or City)	Latitud: LAT	e/Longitude (1) LONG	VA 6th Order HUC (7)	Receiving Water (2)	Name of Impaired Water (9)	Acres	Treated Per B	MP (3) TOTAL	★ BMP Maintenance ID Number (10)	BMP Maintenance Manual (11) SECTION	BMP Inspection Manual (11) SECTION
								-			-		

Geographic Location VA 6th Plan Sheet(s) Type of BMP Installed Date Latitude/Longitude (County or City) Order Receiving Water Name of Impaired (See Table B) HUC (5) (1) (5) (2) Water (9) (5)(7)

(lbs./TP./year) Generating Entity Acquired (6) (12) 4.70 LB/YR

Perpetual Nutrient Credits Acquired for Project

Nutrient Credits

Name of

Nutrient Credit

Tables A and/or B shall be coordinated by the VDOT RLD with the appropriate VDOT District Hydraulics Engineer. The construction plans and the BMP Tables A and/or B are to be formally revised to reflect any authorized/ approved changes to the proposed SWM Plan and/or the proposed BMP construction details. All plan revisions shall be completed in accordance with the Road Design Manual and the Construction Division IIM-CD-2013-12.01, signed and sealed in accordance with Department's sealing and signing policy IIM-LD-243 and filed with the construction record drawings maintained in the VDOT Central Office Plan File Room (ProjectWise). Prior to submitting for termination of coverage under the VPDES General Permit For The Discharge Of Stormwater From Construction Activities, the RLD shall have the District Maintenance Division review the BMPs installed with the project (BMP Table A) for acceptance of maintenance responsibility and to obtain a Maintenance ID number for each BMP listed in BMP Table A. The RLD shall use the information in BMP Tables A and B along with the assigned Maintenance ID number and the date that the BMP became functional as a permanent control measure (for BMPs in Table A only) to complete the LD-445D form when certifying the construction of the BMPs and submitting for

termination of coverage under the VPDES General Permit For

The Discharge Of Stormwater From Construction Activities.

 \bigwedge Any changes to the proposed SWM Plan or BMPs

necessitated during the construction phase of the

project that affects the proposed construction details or potentially affects the informationshown in the BMP

Table A: Permanent BMP Types (1999 Va. SWM Handbook)

Bio-retention Basin Bio-retention Filter Constructed Stormwater Wetlands Extended Detention Basin Extended Detention Basin Enhanced Grassed Swale Infiltration Basin Infiltration Trench Manufactured Treatment Device (MTD) (8) Retention Basin I Retention Basin II Retention Basin III Sand Filter Vegetated Filter Strip

ALTERNATIVE BMP INFORMATION

Table B: Alternative BMP Types Comprehensive SWM Plan (Regional) Facility Pollutant Loading Pro Rata Share Program Other Approved Options (List Type) (4)

Other Approved Types (List Type)

Detention Basin

Table C: Permanent BMP Types (BMP Clearing House)

Sheet Flow to Vegetated Filter Strip Grass Channel Soil Compost Amendment Permeable Pavement (Level 1) Permeable Pavement (Level 2) Infiltration Practice (Level 1) Infiltration Practice (Level 2) Bioretention (Level 1) Bioretention (Level 2)

Dry Swale (Level 1) Dry Swale (Level 2) Wet Swale (Level 1) Wet Swale (Level 2) Filtering Practice (Level 1) Filtering Practice (Level 2) Constructed Wetlands (Level 1) Constructed Wetlands (Level 2) Extended Detention Pond (Level 1) Extended Detention Pond (Level 2)

Wet Pond (Level 1)

Wet Pond (Level 2) Manufactured Treatment Device (MTD)(8) Other Approved Types (List Type)

(1) In decimal degrees to the nearest one ten-thousandth of a degree.

(2) For streams with no names, list "(Unnamed Tributary to downstream name)".

(3) Show acres treated to the nearest one hundreths acre.

(4) Include agreements with off-site BMP owners.

(5) Information pertains to the alternative BMP option location, where applicable. Exception - Not required for nutrient credit purchase option.

(6) Applies to the purchase of nutrient credits only.

(7) Virginia 6th Order HUC (VAHU6) Example - Y030.

(8) Final approved shop drawings of Manufactured Treatment Devices (MTDs) are to be included with the BMP information submitted with the LD-445D form.

(9) List the name of any impaired water to which the BMP discharges. The determination of impaired water shall be based on those streams listed as impaired in the DEQ 2012 305(b)/303(d) Water Quality Assessment Integrated Report and shall be the first named waterbody to which the BMP discharges. The impaired waters are those impaired by sediment, total suspended solids, turbidity, nitrogen or phosphorus.

(10) BMP Maintenance ID Number is to be assigned by the District Maintenance Division at permit termination or project completion. This ID number shall be assigned prior to the permit close out process and entered by the area construction engineer under this column, per IIM-LD-95

(11) Provide the section of each Maintenance manual that pertains to the type of BMP. Both manuals can be found at www.vdot.virginia.gov/ business/manuals in the Maintenance selections. Example: Section 4 would be noted for both the maintenance and inspection manuals for a Bioretention Linfiltration BMP.

(12) Nutrient credits purchased to the nearest one hundredth pound.


Revised 5/1/19


SHEET NO. 0081-095-829 2B(4)

PROJECT MANAGER JAMES JONES, LS, (276) 696-3250 SURVEYED BY, DATE *Woolpert,inc. (757) 549-3549*______ DESIGN BY JAMARA PRITCHARD, P.E., (276) 696-3249 SUBSURFACE UTILITY BY, DATE WOOLPERT INC. (757) 549-3549_____


TEMPORARY SEDIMENT TRAP DETAILS

TEMPORARY SEDIMENT TRAP TABLE												
		SECTION			WET	DRY _	ESTIMATED QUANTITES					
	SEDIMENT TRAP INFORMATION	THRU TEMPORARY	SECTION THRU	SLOPES	STORAGE ELEV.	STORAGE ELEV.	SEDIMENT BASIN EXCAVATION	SILTATION CONTROL EXCAVATION	DRY RIP RAP CLASS I	REMARKS		
		SEDIMENT TRAP	WEIR	(SS)	(C)	(B)	CU. YARDS	CU. YARDS	TONS			
SHEET NO. STATION NO. TRAP NO.	4B STA. 120+25 1	B= 14' W= 44' ELEV. D= 1988' T= 5.0'	L= <u>4.5'</u> Elev. B = <u>1991'</u>	2:1	1989.5'	1991'	85	28	12	TO BE INSTALLED IN EROSION AND SEDIMENT CONTROL PHASE 1 / 1A.		
SHEET NO. STATION NO. TRAP NO.	5B STA. 133+75 2	B= 60' W= 15' ELEV. D= 2018' T= 5.0'	L= <u>10.5'</u> Elev. B = <u>2021'</u>	2:1	2019.5'	2021'	139	60	15	TO BE INSTALLED IN EROSION AND SEDIMENT CONTROL PHASE 1 / 1A.		
SHEET NO. STATION NO. TRAP NO.		B= W= ELEV. D= T=	L= Elev. B =									






PLAN VIEW :TEMPORARY SEDIMENT TRAP NOT TO SCALE



TYPICAL SECTION THRU WEIR ROCK CHECK DAM TYPE I NOT TO SCALE





TYPICAL SECTION (AA)THRU TEMPORARY SEDIMENT TRAP NOT TO SCALE

THESE PLANS ARE UNFINISHED AND UNAPPROVED AND ARE NOT TO BE USED FOR ANY TYPE OF CONSTRUCTION OR THE ACQUISITION OF RIGHT OF WAY.

NEW 6/01 SPECIAL DESIGN SECTION DRAWING NO. A-6


> PROJECT SHEET NO. 2K(I) 0081-095-829





12:15:34 PM

d116156004a.dgn Plotted By: elilley



VA.

DESIGN FEATURES RELATING TO CONSTRUCTION OR TO REGULATION AND CONTROL OF TRAFFIC

MAY BE SUBJECT TO CHANGE AS DEEMED

NECESSARY BY THE DEPARTMENT

REVISED

VDOT Location & Design

Bristol, Virginia HYDRAULIC ENGINEER

TEMP. SEDIMENT TRAP NO.1 DRAINAGE AREA - 0.75 ACRES

R/W_BASED ON CONSTRUCTION BASELINE

UNLESS OTHERWISE NOTED.
FIGURES IN DOUBLE BRACKETS AND DOT-DASHED LINES DENOTES PERMANENT EASEMENTS.
REFERENCE PLAN SHEET 02 (GENERAL NOTES)
FOR EROSION AND SEDIMENT CONTROL LEGEND.

TSF-A

TEMPORARY DIVERSION CHANNEL. TEMP. SEDIMENT TRAP NOVOUTFALL

NOTES:

ROUTE

PROJECT

0081-095-829, RW-201

C-50F

PROPOSED PAVEMENT

PROPOSED FLEXIBLE PAVEMENT PLANING/OVERLAY

DEMOLITION OF PAVEMENT

REFERENCES (PROFILES, DETAIL & DRAINAGE DESCRIPTION SHEETS, ETC.)

Roadway Profile I-81 E&S Legend

SUGGESTED EROSION AND SEDIMENT CONTROL PLANS - PHASE I 0081-095-829

ALL DISTURBED AREAS SHALL DRAIN TO APPROVED EROSION AND SEDIMENT CONTROL FACILITIES AT ALL TIMES DURING LAND DISTURBING ACTIVITIES UNTIL FINAL STABILIZATION IS ACHIEVED. ALL EROSION AND SEDIMENT CONTROL FACILITIES SHALL BE CONSTRUCTED AS A FIRST STEP IN ALL LAND DISTURBING ACTIVITIES AND SHALL BE MADE FUNCTIONAL BEFORE UPSLOPE LAND DISTURBANCE TAKES PLACE.

IMMEDIATELY BEGIN GRADING OPERATION AFTER REMOVING GRASS AND TOPSOIL.


EROSION CONTROL NARRATIVE - PHASE I

INSTALL ROCK CHECK DAMS IN THE EXISTING DITCH LINE AND SILT FENCE ALONG THE TOE OF FILLS AS GRADING OPERATION PROCEEDS UPSTATION.

DOWNSTREAM CONVEYANCES SHOULD BE PLACE AND STABILIZED BEFORE ANY TEMPORARY DIVERSIONS ARE CONSTRUCTED.


THE CONTRACTOR SHALL INSPECT ALL EROSION AND SEDIMENT CONTROL FACILITIES PERIODICALLY AND AFTER EACH RUNOFF-PRODUCING RAINFALL EVENT.ANY NECESSARY REPAIRS OR CLEANUP TO MAINTAIN THE EFFECTIVENESS OF THE EROSION AND SEDIMENT CONTROL FACILITIES SHALL BE MADE IMMEDIATELY. RECORDS OF ALL INSPECTIONS AND REPAIRS MADE TO EROSION AND SEDIMENT CONTROL FACILITIES SHALL BE MAINTAINED BY THE CONTRACTOR.

TEMPORARY STORMWATER CONVEYANCE CHANNEL SCC-I SHALL BE INSTALLED PRIOR TO CONSTRUCTING TEMPORARY SEDIMENT TRAP NO.1



LIMITED ACCESS HIGHWAY

By Resolution of Highway Commission dated October 4, 1956



S/GN

ROJECT MANAGER <u>James Jones, L.S. (276) 696-3257 (Bristol)</u>

SURVEYED BY, DATE <u>Woolpert Inc., (757) 549-3549 (Nov. 24, 2019)</u>
DESIGN BY <u>Tamara Pritchard, P.E. (276) 696-3249 (Bristol)</u>

REVISED

PROJECT

PROJECT

0081-095-829

SCALE

SHEET NO.

ROUTE

d116156005a.dgn

5A


12:16:40 PM Plotted By: elilley LIMITED ACCESS HIGHWAY


By Resolution of Highway Commission dated October 4, 1956 PROJECT MANAGER <u>James Jones, L.S. (276) 696-3257 (Bristol)</u> STATE SHEET NO SURVEYED BY, DATE <u>Woolpert Inc.</u> (757) 549-3549 (Nov.24,2019)

DESIGN BY <u>Tamara Pritchard, P.E. (276) 696-3249 (Bristol)</u> PROJECT ROUTE SUBSURFACE UTILITY BY, DATE ______ 0081-095-829,PE-101; VA. | 081 RW-201, C-501 1-81 NB PROFILE THESE PLANS ARE UNFINISHED
AND UNAPPROVED AND ARE NOT
TO BE USED FOR ANY TYPE
OF CONSTRUCTION OR THE
ACQUISITION OF RIGHT OF WAY. DESIGN FEATURES RELATING TO CONSTRUCTION 2,080 OR TO REGULATION AND CONTROL OF TRAFFIC MAY BE SUBJECT TO CHANGE AS DEEMED NECESSARY BY THE DEPARTMENT VDOT Location & Design 2,075 2,075 Bristol, Virginia ROADWAY ENGINEER 2,070 2,070 MATCH EXIST. SLOPE, SEE CROSS SECTIONS 6A 2,065 2,065 SHEET 2,060 2,060 2.055 2,055 2,050 2,050 MATCH 2,045 2,045 2,040 2,040 STA = 133-43.78 2.035 2,035 EL = 2,040,21 Existing Ground — SSD = 2,246' ex = 1,31' 2,030 2,030 L = 800.00 V = 80 MPH 2,025 2,025 2,020 2,020 2,015 2,015_ 2,010 2,010_ 2,005 2,005 SPLINE GRADE (MATCH EXISTING GRADE) PERCENT OF GRADIENT AND VERTICAL CURVE DATA SHOWN ARE APPROXIMATE 2,000 2,000 1,995 1,995 1,990 1.990 *125+00.00* 132+00.00 *135+00.00* 126+00.00 *127+00.00 128+00.00* 129+00.00 *130+00.00* 131+00.00 *133+00.00 134+00.00 136+00.00 137+00.00* SCALE: I" = 50' HORZ. SHEET NO. /" = 5' VERT. 0081-095-829

SHEET NO.


0081-095-829







12:17:53 PM


d116156006a.dgn Plotted By: elilley



ROJECT MANAGER <u>James Jones, L.S. (276) 696-3257 (Bristol)</u> PROJECT ROUTE URVEYED BY, DATE <u>Woolpert Inc., (757) 549-3549 (Nov. 24, 2019)</u> DESIGN BY <u>Tamara Pritchard,P.E.(276)696-3249 (Bristol)</u> EROSION & SEDIMENT CONTROL PLAN SUBSURFACE UTILITY BY, DATE Woolpert Inc., (757) 549-3549 (Nov. 24, 2019) 0081-095-829, RW-201 VA. C-50i PHASE I PH PLANS DESIGN FEATURES RELATING TO CONSTRUCTION OR TO REGULATION AND CONTROL OF TRAFFIC THESE PLANS ARE UNFINISHED MAY BE SUBJECT TO CHANGE AS DEEMED NECESSARY BY THE DEPARTMENT AND UNAPPROVED AND ARE NOT TO BE USED FOR ANY TYPE VDOT Location & Design OF CONSTRUCTION OR THE Bristol, Virginia HYDRAULICS LEGEND HYDRAULIC ENGINEER ACQUISITION OF RIGHT OF WAY. Denotes Drainage Information Denotes Permanent Rock Check Dams, Ty. 1 ■ Denotes Temporary Rock Check Dams, Ty. II (3-3) Denotes Drainage Structure ____ Denotes Temporary Silt Fence —— Denotes Temporary Filter Barrier Interstate 81 (Southbound) <u>| N/81° 0/3′, 10" E</u> J-81 NB CONSTRUB STANDARD EC-2, TYPE ! Ex. R/W Based On Proj. 0081-095-010, C501, RW-1 ROADWAY ITEMS LEGEND -CONTRACTOR SHALL CLEAN AND MAINTAIN EXISTING PAVED DITCH DURING CONSTRUCTION CONSTRUCTION LIMITS IN CUTS CONSTRUCTION LIMITS IN FILLS PROPOSED PAVEMENT PROPOSED FLEXIBLE PAVEMENT PLANING/OVERLAY DEMOLITION OF PAVEMENT REFERENCES (PROFILES, DETAIL & DRAINAGE EROSION CONTROL NARRATIVE - PHASE I DESCRIPTION SHEETS, ETC.) IMMEDIATELY BEGIN GRADING OPERATION AFTER REMOVING GRASS AND TOPSOIL. ROADWAY PLANS ALL DISTURBED AREAS SHALL DRAIN TO APPROVED EROSION AND SEDIMENT CONTROL FACILITIES AT ALL TIMES DURING LAND DISTURBING ACTIVITIES UNTIL FINAL STABILIZATION IS ACHIEVED.ALL EROSION AND SEDIMENT CONTROL FACILITIES SHALL BE CONSTRUCTED AS A FIRST STEP IN ALL LAND DISTURBING ACTIVITIES AND SHALL BE MADE FUNCTIONAL BEFORE UPSLOPE LAND DISTURBANCE TAKES PLACE. PROFILE 1-81 ESC LEGEND INSTALL ROCK CHECK DAMS IN THE EXISTING DITCH LINE AND SILT FENCE ALONG THE TOE OF FILLS AS GRADING OPERATION PROCEEDS UPSTATION. *NOTES:* DOWNSTREAM CONVEYANCES SHOULD BE PLACE AND STABILIZED BEFORE ANY TEMPORARY DIVERSIONS ARE CONSTRUCTED. R/W BASED ON CONSTRUCTION BASELINE UNLESS OTHERWISE NOTED. FIGURES IN DOUBLE BRACKETS AND DOT-DASHED LINES DENOTES PERMANENT EASEMENTS. REFERENCE PLAN SHEET O2 (GENERAL NOTES) FOR EROSION AND SEDIMENT CONTROL LEGEND. THE CONTRACTOR SHALL INSPECT ALL EROSION AND SEDIMENT CONTROL FACILITIES PERIODICALLY AND AFTER EACH RUNOFF-PRODUCING RAINFALL EVENT.ANY NECESSARY REPAIRS OR CLEANUP TO MAINTAIN THE EFFECTIVENESS OF THE EROSION AND SEDIMENT CONTROL FACILITIES SHALL BE MADE IMMEDIATELY. RECORDS OF ALL INSPECTIONS AND REPAIRS MADE TO EROSION AND SEDIMENT CONTROL FACILITIES SHALL BE MAINTAINED BY THE CONTRACTOR. SUGGESTED EROSION AND SEDIMENT CONTROL PLANS - PHASE I SHEET NO. 0081-095-829








12:19:03 PM

d116156007a**.**dgn Plotted By: elilley

LIMITED ACCESS HIGHWAY


By Resolution of Highway Commission dated October 4, 1956




ROJECT MANAGER *James Jones, L.S. (276) 696-3257 (Bristol)* ROUTE PROJECT URVEYED BY, DATE <u>Woolpert Inc., (757) 549-3549 (Nov. 24, 2019)</u> DESIGN BY <u>Tamara Pritchard, P.E. (276) 696-3249 (Bristol)</u> EROSION & SEDIMENT CONTROL PLAN SUBSURFACE UTILITY BY, DATE Woolpert Inc., (757) 549-3549 (Nov. 24, 2019) 0081-095-829, RW-201 VA. C-50i PHASE I PH PLANS DESIGN FEATURES RELATING TO CONSTRUCTION OR TO REGULATION AND CONTROL OF TRAFFIC THESE PLANS ARE UNFINISHED MAY BE SUBJECT TO CHANGE AS DEEMED NECESSARY BY THE DEPARTMENT AND UNAPPROVED AND ARE NOT TO BE USED FOR ANY TYPE VDOT Location & Design OF CONSTRUCTION OR THE Bristol, Virginia HYDRAULICS LEGEND HYDRAULIC ENGINEER ACQUISITION OF RIGHT OF WAY. 2A Denotes Drainage Information Oenotes Permanent Rock Check Dams, Ty. 1 ◆ Denotes Temporary Rock Check Dams, Ty. II 3-3 Denotes Drainage Structure ____ Denotes Temporary Silt Fence —— Denotes Temporary Filter Barrier Interstate 81 (Southbound) N 181° 03' 10" E , I-81 NB, CONST.R.B Faris Drive Asphalt Pavement ROADWAY ITEMS LEGEND CONSTRUCTION LIMITS IN FILLS PROPOSED PAVEMENT PROPOSED FLEXIBLE PAVEMENT PLANING/OVERLAY DEMOLITION OF PAVEMENT EROSION CONTROL NARRATIVE - PHASE I REFERENCES (PROFILES, DETAIL & DRAINAGE IMMEDIATELY BEGIN GRADING OPERATION AFTER REMOVING GRASS AND TOPSOIL. DESCRIPTION SHEETS, ETC.) ALL DISTURBED AREAS SHALL DRAIN TO APPROVED EROSION AND SEDIMENT CONTROL FACILITIES AT ALL TIMES DURING LAND DISTURBING ACTIVITIES UNTIL FINAL STABILIZATION IS ACHIEVED.ALL EROSION AND SEDIMENT CONTROL FACILITIES SHALL BE CONSTRUCTED AS A FIRST STEP IN ALL LAND DISTURBING ACTIVITIES AND SHALL BE MADE FUNCTIONAL BEFORE UPSLOPE LAND DISTURBANCE TAKES PLACE. ROADWAY PLANS 07 PROFILES 1-81 07A ESC LEGEND INSTALL ROCK CHECK DAMS IN THE EXISTING DITCH LINE AND SILT FENCE ALONG THE TOE OF FILLS AS GRADING OPERATION PROCEEDS UPSTATION. *NOTES:* DOWNSTREAM CONVEYANCES SHOULD BE PLACE AND STABILIZED BEFORE ANY TEMPORARY DIVERSIONS R/W BASED ON CONSTRUCTION BASELINE UNLESS OTHERWISE NOTED. THE CONTRACTOR SHALL INSPECT ALL EROSION AND SEDIMENT CONTROL FACILITIES PERIODICALLY AND AFTER EACH RUNOFF-PRODUCING RAINFALL EVENT. ANY NECESSARY REPAIRS OR CLEANUP TO MAINTAIN THE EFFECTIVENESS OF THE EROSION AND SEDIMENT CONTROL FACILITIES SHALL BE MADE IMMEDIATELY. RECORDS OF ALL INSPECTIONS AND REPAIRS MADE TO EROSION AND SEDIMENT CONTROL FACILITIES SHALL BE MAINTAINED BY THE CONTRACTOR. FIGURES IN DOUBLE BRACKETS AND DOT-DASHED LINES DENOTES PERMANENT EASEMENTS.
REFERENCE PLAN SHEET 02 (GENERAL NOTES)
FOR EROSION AND SEDIMENT CONTROL LEGEND. SUGGESTED EROSION AND SEDIMENT CONTROL PLANS - PHASE I SCALE 0081-095-829

PROJECT MANAGER James Jones, L.S. (276) 696-3257 (Bristol)									REVISED	STATE	STATE SHEET NO.
SURVEYED BY, DATE _Woolpert_Inc., (757) 549-3549 (Nov.24,2019)										ROUTE	PROJECT
DESIGN BY <u>Tamara Pritchard, P.E. (276) 696-3249 (Bristol)</u> SUBSURFACE UTILITY BY, DATE <u>Woolpert Inc.</u> (757) 549-3549 (Nov. 24, 2019)		SION & SI	EDIMEN								0081-095-829, RW-201
										VA. <i>81</i>	C-50i 7C
DH DLANC			PHASI								
PH PLANS					/					JRES RELATING T	
THESE PLANS ARE UNFINISHED									MAY BE SUBJI	ATION AND CONTR ECT TO CHANGE (AS DEEMED
AND UNAPPROVED AND ARE NOT					+				NECESSARY BY	Y THE DEPARTMEN	NT .
TO BE USED FOR ANY TYPE								VDOT Location & Design			
OF CONSTRUCTION OR THE	<u>HYDRAULICS LEGEND</u>							Bristol, Virginia HYDRAULIC ENGINEER			
ACQUISITION OF RIGHT OF WAY.								THE TOTAL CONTROL OF THE PROPERTY OF THE PROPE			
	∕3A Denotes Drai	inage Information			-						
	A Denotes Permai	nent Rock Check Dams, Ty.I									
	Denotes Temporary Rock Check Dams, Ty. II										
	3-3 Denotes Drai	inage Structure									
	Denotes Temp	porary Silt Fence									
	— Denotes Temporary Filter Barrier										
	·										
29										్లు	
	Interstate 81 (Southbound)										
										<u> </u>	
SHS (QLC)	======================================			77 7 0	<u> </u>	:=====================================	======================================				
						9/	91	9	9/		
		/ / / / / / / / / / / / / / / / / / /		_/ / / / / / / /		<u> </u>	, , , , , , , , , , , , , , , , , , , 				
	Nater State 8 N(NarthBound) / / / / / / / / / / / / / / / / / /	Asphált Pavelincat					terstaty 81/(Northbound)		//// /	3.56	
9			Kavak Shouldek XXXX					X GROWN SXI NOW		<u> </u>	
Congrete	(EC-2,Ty.1)			00:		. Concrete S	(20 = , .)	.1)	•	₹	
() () () () () () () () () () () () () (70855 7 7		S S	
	TCD)	OBCO.				Ex Ital Access Based On	Pro i OBS	CURED CURED (TCD	√ <i>N V V V V V V V V V V</i>	
T	X	x x x x	X — X — X — X — X — X — X — X — X — X —	X	X	0081-095-010, C501, RW- 	××	xxx			
DAM ————————————————————————————————————								589		₹ 1	
	z - -	Asphalt Paven	ent Faris L	Drive)		(QLC)	- <u></u> -	- W	
		(mmmmm)	~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~	WB ®MB						~	
	·					Fun					
				II Dr		0081-095-010					
	0.10			Jr dve	Jve/	010, C501, RW-1					
					970					ROA	DWAY ITEMS LEGEND
						(X)				٦	CONSTRUCTION
						80					
						77				<u> </u> F	CONSTRUCTION LIMITS IN FILLS
						[N.]					PROPOSED PAVEMENT
						**************************************					□ □ PROPOSED FLEXIBLE PAVEMENT
						\.\tilde{				, ,,	PROPOSED FLEXIBLE PAVEMENT PLANING/OVERLAY
											DEMOLITION OF PAVEMENT
						\					
EROSION CONTROL NARRATIVE - PHASE II											REFERENCES
											DFILES, DETAIL & DRAINAGE
I. ALL DISTURBED AREAS SHALL DRAIN T	TO APPROVED EROSION AND SEL	DIMENT								DE.	SCRIPTION SHEETS, ETC.)
I. ALL DISTURBED AREAS SHALL DRAIN T CONTROL FACILITIES AT ALL TIMES DU FINAL STABILIZATION IS ACHIEVED.ALL SHALL BE CONSTRUCTED AS A FIRST SHALL BE MADE FUNCTIONAL BEFORE	IRING LAND DISTURBING ACTIVITI	ES UNTIL								ROA	DWAY PLANS 07
SHALL BE CONSTRUCTED AS A FIRST	STEP IN ALL LAND DISTURBING	ACTIVITIES AND									OFILES 1-81 O7A
SHALL BE MADE FUNCTIONAL BEFORE	UPSLOPE LAND DISTURBANCE	TAKES PLACE.									LEGEND 2
2. INSTALL ROCK CHECK DAMS IN THE E. TOE OF FILLS AS GRADING OPERATION	XISTING_DITCH_LINE_AND_SILT_I	FENCE ALONG THE									
TOE OF FILLS AS GRADING OPERATION	N PROCEEDS UPSTATION.				NOTES:						
3. DOWNSTREAM CONVEYANCES SHOULD E TEMPORARY DIVERSIONS ARE CONSTRU	BE_PLACE AND STABILIZED BEF	FORE ANY				D ON CONCEDUCTION					
					I. R/W BASE UNLESS 07	D ON CONSTRUCTION HERWISE NOTED.	I BASINLINE				
4. THE CONTRACTOR SHALL INSPECT ALL	EROSION AND SEDIMENT CONTI	ROL FACILITIES			2. FIGURES II	N DOUBLE BRACKETS	S AND DOT-DASHED				
ANY NECESSARY REPAIRS OR CIFANUP	PROUDUCING KAINFALL EVENT. PROMAINTAIN THE FEFECTIVE.	NESS OF THF			3. <u>REFERENC</u>	E PLAN SHEET 02	(GENERAL NOTES)				
TEMPORARY DIVERSIONS ARE CONSTRUCTED. 4. THE CONTRACTOR SHALL INSPECT ALL EROSION AND SEDIMENT CONTROL FACILITIES 4. THE CONTRACTOR SHALL INSPECT ALL EROSION AND SEDIMENT CONTROL FACILITIES 4. THE CONTRACTOR SHALL INSPECT ALL EROSION AND SEDIMENT CONTROL FACILITIES 4. THE CONTRACTOR SHALL INSPECT ALL EROSION AND SEDIMENT CONTROL FACILITIES IN DOUBLE BRACKETS 4. THE CONTRACTOR SHALL INSPECT ALL EROSION AND SEDIMENT CONTROL FACILITIES OF ALL INSPECTIONS AND REPAIRS MADE TO EROSION AND SEDIMENT CONTROL FACILITIES SHALL BE MAINTAINED BY THE CONTRACTOR.							CONTROL LEGEND.			SUGGEST	ED EROSION AND SEDIMENT
RECURDS OF ALL INSPECTIONS AND RECORDS OF ACILITIES SHALL BE MAINTA	AINED BY THE CONTRACTOR.	SEDIMENI									CONTROL PLANS - PHASE II
										SCALE	_
									Ö	50'	

LIMITED ACCESS HIGHWAY By Resolution of Highway Commission dated October 4, 1956



BRIST



LIMITED ACCESS HIGHWAY

By Resolution of Highway Commission dated October 4, 1956 PROJECT MANAGER <u>James Jones, L.S. (276) 696-3257 (Bristol)</u> STATE SHEET NO SURVEYED BY, DATE <u>Woolpert Inc.</u> (757) 549-3549 (Nov.24,2019)

DESIGN BY <u>Tamara Pritchard, P.E. (276) 696-3249 (Bristol)</u> PROJECT ROUTE 0081-095-829,PE-101; SUBSURFACE UTILITY BY, DATE ______ VA. | 081 RW-201, C-501 1-81 NB PROFILE THESE PLANS ARE UNFINISHED
AND UNAPPROVED AND ARE NOT
TO BE USED FOR ANY TYPE
OF CONSTRUCTION OR THE
ACQUISITION OF RIGHT OF WAY. DESIGN FEATURES RELATING TO CONSTRUCTION OR TO REGULATION AND CONTROL OF TRAFFIC MAY BE SUBJECT TO CHANGE AS DEEMED NECESSARY BY THE DEPARTMENT VDOT Location & Design Bristol, Virginia ROADWAY ENGINEER 2,130_ 2,130 MATCH EXIST SLOPE, SEE CROSS SECTIONS 2,125 2,125 2,120 2,120 STA.166+00.00 END TRUCK 2,115 2.115 CLIMBING LANE END PROJECT 0081-095-829,0-501 STATION 172.00.00 2,110 END PROJECT 0081-095-829, RW-201 2,110 STATION 169.86.13 STA. 172+00.00 END TAPER — Existing Ground FOR LANE DROP 2,105 2,105 2,100 2,100 2,095 2,095 2,090 2,090 END PROJECT 0081-095-829, PE-101 2,085 2,085 STATION 177.00.00 2,080 2,080 2,075 2,075 2,070 2,070 2,065 2,065 SPLINE GRADE (MATCH EXISTING GRADE) PERCENT OF GRADIENT AND VERTICAL CURVE DATA SHOWN ARE APPROXIMATE 2,060 2,060 2,055 2,055 2.050 2,050 164+00.00 *167+00.00 168+00.00 169+00.00 170+00.00 171+00.00 173+00.00 175+00.00 176+00.00 177+00.00 165+00.00 166+00.00 172+00.00 174+00.00* SCALE: I" = 50' HORZ. SHEET NO. 0081-095-829 /" = 5' VERT.

EROSION CONTROL NARRATIVE - PHASE I

IMMEDIATELY BEGIN GRADING OPERATION AFTER REMOVING GRASS AND TOPSOIL.

INSTALL ROCK CHECK DAMS IN THE EXISTING DITCH LINE AND SILT FENCE ALONG THE TOE OF FILLS AS GRADING OPERATION PROCEEDS UPSTATION.

DOWNSTREAM CONVEYANCES SHOULD BE PLACE AND STABILIZED BEFORE ANY TEMPORARY DIVERSIONS ARE CONSTRUCTED.

THE CONTRACTOR SHALL INSPECT ALL EROSION AND SEDIMENT CONTROL FACILITIES PERIODICALLY AND AFTER EACH RUNOFF-PRODUCING RAINFALL EVENT.ANY NECESSARY REPAIRS OR CLEANUP TO MAINTAIN THE EFFECTIVENESS OF THE EROSION AND SEDIMENT CONTROL FACILITIES SHALL BE MADE IMMEDIATELY. RECORDS OF ALL INSPECTIONS AND REPAIRS MADE TO EROSION AND SEDIMENT CONTROL FACILITIES SHALL BE MAINTAINED BY THE CONTRACTOR.


(PROFILES, DETAIL & DRAINAGE DESCRIPTION SHEETS, ETC.) ALL DISTURBED AREAS SHALL DRAIN TO APPROVED EROSION AND SEDIMENT CONTROL FACILITIES AT ALL TIMES DURING LAND DISTURBING ACTIVITIES UNTIL FINAL STABILIZATION IS ACHIEVED.ALL EROSION AND SEDIMENT CONTROL FACILITIES SHALL BE CONSTRUCTED AS A FIRST STEP IN ALL LAND DISTURBING ACTIVITIES AND SHALL BE MADE FUNCTIONAL BEFORE UPSLOPE LAND DISTURBANCE TAKES PLACE.

ROADWAY PLAN

PROFILE 1-81 ESC LEGEND

SUGGESTED EROSION AND SEDIMENT CONTROL PLANS - PHASE I SHEET NO.

0081-095-829



LIMITED ACCESS HIGHWAY

By Resolution of Highway Commission dated October 4, 1956

